

INDUSTRIAL COMPONENT DATA

40071352152 CEILINGMOUNTINGSET FOR SPIRITELED 16 EATON ELECTRIC CEILINGMOUNTINGSET FOR SPIRITELED 16

Brand: EATON - MOELLER | Manufacturer Part Number: 40071352152



Manufacturer	EATON - MOELLER
MPN / Reference	40071352152
Catalog number	CEILINGMOUNTINGSET FOR SPIRITELED 16
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-9C730359C1
Generated	2026-08-06

Product Overview

CEILINGMOUNTINGSET FOR SPIRITELED 16

Eaton SpiritLED 16 CG-S, Recessed Ceiling installation kit with rope suspension, incl. LED supply

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Central Battery System

Additional Product Information

General specifications

Product Name Eaton SpiritLED CG-S Emergency luminaire Catalog Number 40071352152 EAN 4012539316466 Product Length/Depth 200 mm Product Height 45 mm Product Width 90 mm Product Weight 0.24 kg Certifications CE Product specifications

Battery quality Not applicable Permissible ambient temperature - min -10 °C Permissible ambient temperature - max 40 °C Protection class II Degree of impact resistance (IK) IK 03 Outdoor use compliance False Explosion protected False Degree of protection IP41 Mode Maintained / Non-Maintained (M / NM) Monitoring equipment Safety module for monitoring (central feeded system) Power supply system Central (central battery) Voltage type AC/DC Current Consumption At 220V DC 7 mA Apparent Power At Mains Operation 3.8 VA Effective power at mains operation 1.7 W Wiring system Continuous circuit/emergency circuit With remote switch connection True Reserve-polarity protected True Conductor cross section 2.5 Connection type Plug-in connection Type of control gear LED operating device voltage-controlled Type of wiring Ending Nominal voltage AC - max 240 V Nominal voltage AC - min 220 V Nominal voltage DC 220 V Rated ambient temp acc.

IEC62722-2-1 - Min -10 °C Rated ambient temp acc. IEC62722-2-1 - Max 40 °C Inrush current 1.5 Mounting Method Built-in
Material housing Plastic Color housing Grey Number Of Poles (Numeric) 2 Impact strength IK03 Kind of luminaire Exit sign
luminaire Energy efficiency class of the built-in lamp A++, A+, A (LED...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 40071352152 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.