

INDUSTRIAL COMPONENT DATA

T0-1-8220/XZ 009563 Y7-9563 EATON ELECTRIC

Changeoverswitches, Contacts: 2, 20 A, 90 °, rear mounting, Basic..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-1-8220/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-1-8220/XZ
Catalog number	Y7-9563
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-996724B5BA
Generated	2026-08-05

Product Overview

Changeoverswitches, Contacts: 2, 20 A, 90 °, rear mounting, Basic switch

Switch 2-pole switch 20 A Indicator plate: 1-2 90°

Changeoverswitches, T0, 20 A, rear mounting, Basic switch, 1 contact unit(s), Contacts: 2, 90 °, design no. 8220

Changeover switch, Product range: Control switches, Part group reference: T0, Contacts: 2, Design: rear mounting, Basic switch, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

EL-Nummer (Norway)1456670Changeoverswitches, T0, 20 A, rear mounting, Basic switch, 1 contact unit(s), Contacts: 2, 90 °, design no. 8220Changeover switch, Product range: Control switches, Part group reference: T0, Contacts: 2, Design: rear mounting, Basic switch, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3Delivery program

Product rangeControl switchesPart group referenceT0Basic functionChangeoverswitchesContacts2Designrear mounting
Basic switchContact sequenceSwitching angle90 °Design number8220Front plate no.Motor rating AC-23A, 50 - 60 Hz
[P]400 V [P]5.5 kWRated uninterrupted current [Iu]20 ANote on rated uninterrupted current IuRated uninterrupted current

luis specified for max. cross-section. Number of contact units 1 contact unit(s) Technical data
General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204
Switch-disconnector according to IEC/EN 60947-3 Climatic proofing Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open-25 - +50 °C Ambient temperature Enclosed-25 - +40
°C Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [Uimp] 6000 V AC Mechanical shock
resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [Ue] 690 V
AC Electrical characteristics Rated uninterrupted current [Iu] 20 A Elec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-1-8220/XZ with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.