

INDUSTRIAL COMPONENT DATA

QM40/3N 1319970 Y8-1319970 EATON ELECTRIC Changeover switch, 2x4p, 40A, switch-disconnector

Brand: EATON - MOELLER | Manufacturer Part Number: QM40/3N



Manufacturer	EATON - MOELLER
MPN / Reference	QM40/3N
Catalog number	Y8-1319970
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-A007402FC9
Generated	2026-08-02

Product Overview

Changeover switch, 2x4p, 40A, switch-disconnector

QM40/3N

Eaton QM Changeover switch, QM, 40 A, 2 x 3 pole + N (switched), without rotary handle, With drive shaft, 6 mm square

Switch-disconnector QM40/3N, changeover switch, 2x4 pole (3P + switched N), free air thermal current I_{the} 40 A, with shaft 6mm square

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

General specifications

Product Name Eaton QM Changeover switch Catalog Number 1319970 Model Code QM40/3N EAN 8711426315396

Product Length/Depth 125 mm Product Height 90 mm Product Width 125 mm Product Weight 0.49 kg Certifications IEC/EN 60947

CE

IEC/EN 60947-3

IEC/EN 60204

VDE 0660

RoHS Features & Functions

Fitted with: Drive shaft Functions Optional Stop Function Number of poles Eight-pole General

Accessories Auxiliary contact fitted by user. Actuator type Other Degree of protection NEMA Other Degree of protection

(front side) IP20 Mounting method Top-hat rail mounting

Rear mounting Mounting position As required Overvoltage category III Pollution degree 3 Product Category Changeover switches Rated impulse withstand voltage (Uimp) 6000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Suitable for Ground mounting Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 2.5 - 16 mm², solid

1 x (2.5 - 10) mm², flexible Stripping length (main cable) 10 mm Tightening torque 1.8 Nm, Screw terminals, Main cables

Tightening torque 1.8 Nm, Screw terminals, Main cables Electrical rating

Rated conditional short-circuit current (Iq) 0 kA Rated insulation voltage (Ui) 690 V Rated operational power at AC-23A, 400 V, 50 Hz 15 kW Rated operational power at AC-3, 380/400 V, 50 Hz 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / QM40/3N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.