

INDUSTRIAL COMPONENT DATA

QM40/3N 1319970 Y8-1319970 EATON ELECTRIC Changeover switch, 2x4p, 40A, switch-disconnector

Brand: EATON - MOELLER | Manufacturer Part Number: QM40/3N



Manufacturer	EATON - MOELLER
MPN / Reference	QM40/3N
Catalog number	Y8-1319970
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-A007402FC9
Generated	2026-08-04

Product Overview

Changeover switch, 2x4p, 40A, switch-disconnector

QM40/3N

Eaton QM Changeover switch, QM, 40 A, 2 x 3 pole + N (switched), without rotary handle, With drive shaft, 6 mm square

Switch-disconnector QM40/3N, changeover switch, 2x4 pole (3P + switched N), free air thermal current Ithe 40 A, with shaft 6mm square

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

General specifications

Product Name Eaton QM Changeover switch Catalog Number 1319970 Model Code QM40/3N EAN 8711426315396

Product Length/Depth 125 mm Product Height 90 mm Product Width 125 mm Product Weight 0.49 kg Certifications IEC/EN 60947

CE

IEC/EN 60947-3

IEC/EN 60204

VDE 0660

RoHS Features & Functions

Fitted with: Drive shaft Functions Optional Stop Function Number of poles Eight-pole General

Accessories Auxiliary contact fitted by user. Actuator type Other Degree of protection NEMA Other Degree of protection

(front side) IP20 Mounting method Top-hat rail mounting

Rear mounting Mounting position As required Overvoltage category III Pollution degree 3 Product Category Changeover switches Rated impulse withstand voltage (Uimp) 6000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Suitable for Ground mounting Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 2.5 - 16 mm², solid

1 x (2.5 - 10) mm², flexible Stripping length (main cable) 10 mm Tightening torque 1.8 Nm, Screw terminals, Main cables

Tightening torque 1.8 Nm, Screw terminals, Main cables Electrical rating

Rated conditional short-circuit current (Iq) 0 kA Rated insulation voltage (Ui) 690 V Rated operational power at AC-23A, 400 V, 50 Hz 15 kW Rated operational power at AC-3, 380/400 V, 50 Hz 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / QM40/3N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.