

INDUSTRIAL COMPONENT DATA

T0-3-8212/XZ 005740 Y7-5740 EATON ELECTRIC

Changeoverswitches, Contacts: 6, 20 A, 60 °, rear mounting, Basic..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-8212/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-8212/XZ
Catalog number	Y7-5740
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-A89F787E2E
Generated	2026-08-05

Product Overview

Changeoverswitches, Contacts: 6, 20 A, 60 °, rear mounting, Basic switch

Switch 6-pole switch 20 A Indicator plate: 1-0-2 60°

Changeoverswitches, T0, 20 A, rear mounting, Basic switch, 3 contact unit(s), Contacts: 6, 60 °, design no. 8212

Changeover switch, Product range: Control switches, Part group reference: T0, Contacts: 6, Design: rear mounting, Basic switch, Switching angle: 60 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

EL-Nummer (Norway)1456661Changeoverswitches, T0, 20 A, rear mounting, Basic switch, 3 contact unit(s), Contacts: 6, 60 °, design no. 8212Changeover switch, Product range: Control switches, Part group reference: T0, Contacts: 6, Design: rear mounting, Basic switch, Switching angle: 60 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3Delivery program

Product rangeControl switchesPart group referenceT0Basic functionChangeoverswitchesContacts6Designrear mounting
Basic switchContact sequenceSwitching angle60 °Design number8212Front plate no.Motor rating AC-23A, 50 - 60 Hz
[P]400 V [P]5.5 kWRated uninterrupted current [Iu]20 ANote on rated uninterrupted current IuRated uninterrupted current

luis specified for max. cross-section.Number of contact units3 contact unit(s)Technical data
GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204
Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +50 °CAmbient temperatureEnclosed-25 - +40
°COvervoltage category/pollution degreeIII/3Rated impulse withstand voltage [Uimp]6000 V ACMechanical shock
resistance15 gMounting positionAs requiredContactsElectrical characteristicsRated operational voltage [Ue]690 V
ACElectrical characteristicsRated uninterrupted current [Iu]20 AElec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-8212/XZ with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.