

INDUSTRIAL COMPONENT DATA

T0-4-8213/IVS 081559 Y7-81559 EATON ELECTRIC

Changeoverswitches, Contacts: 8, 20 A, front plate: 1-0-2, 60 °

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-8213/IVS



Manufacturer	EATON - MOELLER
MPN / Reference	T0-4-8213/IVS
Catalog number	Y7-81559
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-8823035D47
Generated	2026-08-06

Product Overview

Changeoverswitches, Contacts: 8, 20 A, front plate: 1-0-2, 60 °, maintained, service distribution board mounting

Switch Switch; 8 poles; 20 A; Indicator plate: 1-0-2; 60 °;

Eaton Moeller® series T0 Changeoverswitches, T0, 20 A, service distribution board mounting, 4 contact unit(s), Contacts: 8, 60 °, maintained, With 0 (Off) position, 1-0-2, Design number 8213

Changeover switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 8, Degree of Protection: Front IP30, Design: service distribution board mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 1-0-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Changeover switch Catalog Number 081559 Model Code T0-4-8213/IVS EAN 4015080815594 Product Length/Depth 111 mm Product Height 55 mm Product Width 54 mm Product Weight 0.179 kg

Certifications CSA Class No.: 3211-05

IEC/EN 60947-3

UL File No.: E36332
CSA-C22.2 No. 60947-4-1-14
UL 60947-4-1
CE
VDE 0660
IEC/EN 60947
CSA-C22.2 No. 94
CSA File No.: 012528
UL
IEC/EN 60204
UL Category Control No.: NLRV
CSA Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 081559 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Model (EF000010)
Reverser
Number of poles (EF001391)
4
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Rated permanent current Iu (EF001389)
20 A
Rated operation current Ie at AC-3, 400 V (EF001392)
11.5 A
Rated operation power at AC-3, 400 V (EF001364)
4 kW
Degree of protection (IP), front side (EF003118)
IP30
Degree of protection (NEMA), front side (EF011961)
2
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Suitable for floor mounting (EF007243)
Yes
Suitable for front mounting (EF007246)
No
Suitable for distribution board installation (EF007262)
Yes
Suitable for intermediate mounting (EF007264)
No

Complete device in housing (EF007317)

No

Housing material (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-8213/IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.