

INDUSTRIAL COMPONENT DATA

T3-3-8451/I2 207189 Y7-207189 EATON ELECTRIC

Changeoverswitches, Contacts: 6, 32 A, front plate: 0-1-2, 60 °

Brand: EATON - MOELLER | Manufacturer Part Number: T3-3-8451/I2



Manufacturer	EATON - MOELLER
MPN / Reference	T3-3-8451/I2
Catalog number	Y7-207189
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-40F8156FE9
Generated	2026-08-05

Product Overview

Changeoverswitches, Contacts: 6, 32 A, front plate: 0-1-2, 60 °, maintained, surface mounting

T3-3-8451/I2

Eaton Moeller® series T3 Changeoverswitches, T3, 32 A, surface mounting, 3 contact unit(s), Contacts: 6, 60 °, maintained, With 0 (Off) position, 0-1-2, Design number 8451

Changeover switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 6, Degree of Protection: IP65, Design: surface mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Changeover switch Catalog Number 207189 Model Code T3-3-8451/I2 EAN 4015082071899 Product Length/Depth 181 mm Product Height 127 mm Product Width 100 mm Product Weight 0.563 kg
Certifications CSA Class No.: 3211-05
CSA file No. 012528

IEC/EN 60947-3

IEC/EN 60947

VDE 0660

IEC/EN 60204

CSA

UL

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14

CSA-C22.2 No. 94

CE marking

UL Category Control No.: NLRV

UL File No.: E36332

UL Listed

CSA certified

ETIM for 207189 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

32 A

Rated operation current I_e at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

Yes

Housing material (EF001596)

Plastic

Type of control element (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-3-8451/I2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.