

## INDUSTRIAL COMPONENT DATA

# T3-5-8369/I2 207536 Y7-207536 EATON ELECTRIC

## Changeoverswitches, Contacts: 10, 32 A, front plate: 1-2, 90 °, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-5-8369/I2



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T3-5-8369/I2    |
| Catalog number  | Y7-207536       |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-664E95B3FB   |
| Generated       | 2026-08-05      |

## Product Overview

Changeoverswitches, Contacts: 10, 32 A, front plate: 1-2, 90 °, maintained, surface mounting  
T3-5-8369/I2

Eaton Moeller® series T3 Changeoverswitches, T3, 32 A, surface mounting, 5 contact unit(s), Contacts: 10, 90 °, maintained, Without 0 (Off) position, 1-2, Design number 8369

Changeover switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 10, Degree of Protection: IP65, Design: surface mounting, Switching angle: 90 °, Switching performance: maintained, Without 0 (Off) position, front plate: 1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I<sub>u</sub> = 32 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

## Additional Product Information

## General specifications

Product Name Eaton Moeller® series T3 Changeover switch Catalog Number 207536 Model Code T3-5-8369/I2 EAN 4015082075361 Product Length/Depth 181 mm Product Height 180 mm Product Width 100 mm Product Weight 0.634 kg  
Compliances CE Marked Certifications CSA Std. C22.2 No. 14-05  
UL 508

IEC 60947  
EN 60947-3  
VDE  
UL Category Control No.: NLRV  
IEC/EN 60204  
CSA-C22.2 No. 94  
CSA-C22.2 No. 60947-4-1-14  
UL 60947-4-1  
IEC/EN 60947  
IEC/EN 60947-3  
UL  
CE  
CSA File No.: 012528  
UL File No.: E36332  
CSA Class No.: 3211-05  
CSA  
VDE 0660 Catalog Notes Rated Short-time Withstand Current (I<sub>cw</sub>) for a time of 1 second  
ETIM for 207536 Low-voltage industrial controls and switchgear (EC001105)  
Feature Name  
Feature Value  
Model (EF000010)  
Reverser  
Number of poles (EF001391)  
5  
With zero (off) position (EF001416)  
No  
With retraction in 0-position (EF002428)  
No  
Rated permanent current I<sub>u</sub> (EF001389)  
32 A  
Rated operation current I<sub>e</sub> at AC-3, 400 V (EF001392)  
23.7 A  
Rated operation power at AC-3, 400 V (EF001364)  
12 kW  
Degree of protection (IP), front side (EF003118)  
IP65  
Degree of protection (NEMA), front side (EF011961)  
12  
Number of auxiliary contacts as normally closed contact (EF001377)  
0  
Number of auxiliary contacts as normally open contact (EF001376)  
0  
Number of auxiliary contacts as change-over contact (EF003531)  
0  
Suitable for floor mounting (EF007243)  
Yes  
Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mou...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-5-8369/I2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.