

INDUSTRIAL COMPONENT DATA

T3-7-8363/EZ 005574 Y7-5574 EATON ELECTRIC

Changeoverswitches, Contacts: 14, 32 A, front plate: 1-0-2, 60 °, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-7-8363/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-7-8363/EZ
Catalog number	Y7-5574
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-F21B2B0948
Generated	2026-08-03

Product Overview

Changeoverswitches, Contacts: 14, 32 A, front plate: 1-0-2, 60 °, maintained, centre mounting

Switch Switch 14 poles 32 A Indicator plate: 1-0-2 60°

Eaton Moeller® series T3 Changeoverswitches, T3, 32 A, centre mounting, 7 contact unit(s), Contacts: 14, 60 °, maintained, With 0 (Off) position, 1-0-2, Design number 8363

Changeover switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 14, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 1-0-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 7 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Changeover switch Catalog Number 005574 Model Code T3-7-8363/EZ EAN 4015080055747 Product Length/Depth 170 mm Product Height 54 mm Product Width 61 mm Product Weight 0.372 kg

Certifications CE

CSA-C22.2 No. 94

IEC/EN 60947

CSA Class No.: 3211-05

IEC/EN 60204

CSA File No.: 012528

CSA-C22.2 No. 60947-4-1-14

UL File No.: E36332

UL Category Control No.: NLRV

UL 60947-4-1

VDE 0660

CSA

UL

IEC/EN 60947-3 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 005574 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

7

With zero (off) position (EF001416)

true

With retraction in 0-position (EF002428)

false

Rated permanent current Iu (EF001389)

32 A

Rated operation current Ie at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

false

Suitable for front mounting (EF007246)

true

Suitable for distribution board installation (EF007262)

false

Suitable for intermediate mounting (EF007264)

false

Complete device in housing (EF007317)

false

Ho...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-7-8363/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.