

## INDUSTRIAL COMPONENT DATA

# T0-1-78/E 009369 Y7-9369 EATON ELECTRIC

## Changeoverswitches, Contacts: 2, 20 A, front plate: 2-0-1, 90 °, mai..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-1-78/E



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T0-1-78/E       |
| Catalog number  | Y7-9369         |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-CE18126E87   |
| Generated       | 2026-08-03      |

### Product Overview

Changeoverswitches, Contacts: 2, 20 A, front plate: 2-0-1, 90 °, maintained, flush mounting

Switch Switch; 2-pole; 20a; rating Plate: 2-0-1; 90 °; Mounting

Eaton Moeller® series T0 Changeoverswitches, T0, 20 A, flush mounting, 1 contact unit(s), Contacts: 2, 90 °, maintained, With 0 (Off) position, 2-0-1, Design number 78

Changeover switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 2, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

### Additional Product Information

## General specifications

Product Name Eaton Moeller® series T0 Changeover switch Catalog Number 009369 Model Code T0-1-78/E EAN 4015080093695 Product Length/Depth 76 mm Product Height 48 mm Product Width 48 mm Product Weight 0.083 kg  
Certifications IEC/EN 60204  
IEC/EN 60947-3

UL Category Control No.: NLRV

CSA File No.: 012528

IEC/EN 60947

CSA Class No.: 3211-05

CSA

UL

UL File No.: E36332

VDE 0660

CE

CSA-C22.2 No. 94

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second  
ETIM for 009369 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

1

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (EF0015...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-1-78/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.