

INDUSTRIAL COMPONENT DATA

T0-1-78/Z 009375 Y7-9375 EATON ELECTRIC

Changeoverswitches, Contacts: 2, 20 A, front plate: 2-0-1, 90 °, mai..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-1-78/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-1-78/Z
Catalog number	Y7-9375
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-BDE21F9ADF
Generated	2026-08-04

Product Overview

Changeoverswitches, Contacts: 2, 20 A, front plate: 2-0-1, 90 °, maintained, rear mounting

Switch Switch; 2-pole; 20a; rating Plate: 2-0-1; 90 °; Mounting bottom panel

Eaton Moeller® series T0 Changeoverswitches, T0, 20 A, rear mounting, 1 contact unit(s), Contacts: 2, 90 °, maintained, With 0 (Off) position, 2-0-1, Design number 78

Changeover switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 2, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 90 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Changeover switch Catalog Number 009375 Model Code T0-1-78/Z EAN

4015080093756 Product Length/Depth 118 mm Product Height 48 mm Product Width 48 mm Product Weight 0.112 kg

Certifications UL File No.: E36332

UL Category Control No.: NLRV

CSA-C22.2 No. 60947-4-1-14

UL

IEC/EN 60204

CSA

VDE 0660

IEC/EN 60947-3

IEC/EN 60947

CSA Class No.: 3211-05

CSA-C22.2 No. 94

CE

CSA File No.: 012528

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 009375 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

1

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Housing material (EF00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-1-78/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.