

INDUSTRIAL COMPONENT DATA

T3-11-8367/Z 003914 Y7-3914 EATON ELECTRIC

Changeoverswitches, Contacts: 22, 32 A, front plate: 1-0-2, 45 °, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-11-8367/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T3-11-8367/Z
Catalog number	Y7-3914
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-EA60853D1E
Generated	2026-08-04

Product Overview

Changeoverswitches, Contacts: 22, 32 A, front plate: 1-0-2, 45 °, maintained, rear mounting

Switch 2-pole2 32 A Indicator plate: 1-0-2 45°

Eaton Moeller® series T3 Changeoverswitches, T3, 32 A, rear mounting, 11 contact unit(s), Contacts: 22, 45 °, maintained, With 0 (Off) position, 1-0-2, Design number 8367

Changeover switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 22, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, front plate: 1-0-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 11 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Changeover switch Catalog Number 003914 Model Code T3-11-8367/Z EAN 4015080039143 Product Length/Depth 236 mm Product Height 54 mm Product Width 61 mm Product Weight 0.566 kg Certifications CSA-C22.2 No. 60947-4-1-14 IEC/EN 60947-3

UL File No.: E36332

CSA Class No.: 3211-05

IEC/EN 60204

UL 60947-4-1

VDE 0660

UL

CSA-C22.2 No. 94

IEC/EN 60947

UL Category Control No.: NLRV

CE

CSA

CSA File No.: 012528 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 003914 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

11

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

32 A

Rated operation current Ie at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Housing material....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-11-8367/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.