

INDUSTRIAL COMPONENT DATA

T0-2-8517/EZ 011848 Y7-11848 EATON ELECTRIC

Changeoverswitches, Contacts: 3, 20 A, front plate: Betrieb-Aus-..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-8517/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-8517/EZ
Catalog number	Y7-11848
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-E4710E4E22
Generated	2026-08-05

Product Overview

Changeoverswitches, Contacts: 3, 20 A, front plate: Betrieb-Aus-Einrichten, 90 °, maintained, centre mounting
Switch Switch; 3-pole; 20a; rating Plate: Betrieb-Aus-Einrichten; 90 °; Mounting with central fixing
Eaton Moeller® series T0 Changeoverswitches, T0, 20 A, centre mounting, 2 contact unit(s), Contacts: 3, 90 °, maintained, Without 0 (Off) position, Betrieb-Aus-Einrichten, Design number 8517
Changeover switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 3, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 90 °, Switching performance: maintained, Without 0 (Off) position, 2 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: Betrieb-Aus-Einrichten

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Changeover switch Catalog Number 011848 Model Code T0-2-8517/EZ EAN 4015080118480 Product Length/Depth 106 mm Product Height 48 mm Product Width 48 mm Product Weight 0.124 kg
Certifications VDE 0660
UL 60947-4-1

CE

IEC/EN 60947

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-3

CSA

UL

CSA-C22.2 No. 94

CSA File No.: 012528

CSA Class No.: 3211-05

UL Category Control No.: NLRV

UL File No.: E36332

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 011848 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Reverser

Number of poles (EF001391)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

3

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-8517/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.