

INDUSTRIAL COMPONENT DATA

CHM2DU EATON ELECTRIC Fused disconnector, low voltage, 30 A, AC 240 V, UL midget, IEC 10 x 38, AC23A, 1P, UL..

Brand: EATON - MOELLER | Manufacturer Part Number: CHM2DU



Manufacturer	EATON - MOELLER
MPN / Reference	CHM2DU
Catalog number	10000
Category	Holder for cylindrical fuse
Minimum order	6 Pcs
Document ID	EO-A9E9E43E49
Generated	2026-08-06

Product Overview

2Pole 30A 600V MFH For 10X38 Midget fuse

2Pole 30A 600V MFH For 10X38 Midget fuse - Fuse holder, low voltage, 32 A, AC 690 V, 10 x 38 mm, 2P, UL, IEC
MODULAR FUSE HOLDER, MODULAR, 30A (UL),

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse holder, low voltage, 32 A, AC 690 V, 10 x 38 mm, 2P, UL, IEC
Fuse accessory, fuse-holder, low voltage, 32 A, AC 690 V, 10 x 38 mm, 2P, UL, IEC, DIN rail mounting, modular, colour-coded, Rated for use with 75°C or 90°C wire, fine stranded wire, spade terminals and with comb-bus bars., Use any higher temperature rated wire with appropriate derating., for cylindrical fuse-links, for midget fuses, IEC, cULus, CCC, CSA, UR
Delivery program

Product range
Fuse accessory
Basic function
Fuse-holder
Field of application
low voltage
Rated current [I]
32 A
Rated voltage
AC 690 V
Size
10 x 38 mm
Description
DIN rail mounting
colour-coded

Rated for use with 75°C or 90°C wire

fine stranded wire

spade terminals and with comb-bus bars

Use any higher temperature rated wire with appropriate derating.

Modular
Number of poles
2P
usable for size/applications
for cylindrical fuse-links
for midget fuses
Standard/Approval
UL

IECStandards/RegulationsIEC

cULus

CCC

CSA

URTechnical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Holder for cylindrical fuse (EC002705)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Holder for cylindrical fuse ( [ADI305007])Nominal voltage690 VMounting methodDIN railFor fuse size10x38 mmNumber of poles2Concurrently switching N-neutralNoLockableYesOptical defect indicationNoWidth in number of modular spacings2Built-in depth45.1 mmDegree of protection (IP)Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CHM2DU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.