

INDUSTRIAL COMPONENT DATA

CHPV2IU EATON ELECTRIC Fuse-link, high speed, 100 A, DC 1500 V, 01XL, 43 x 193 mm, gPV, IEC, UL, with indica..

Brand: EATON - MOELLER | Manufacturer Part Number: CHPV2IU



Manufacturer	EATON - MOELLER
MPN / Reference	CHPV2IU
Catalog number	10000
Category	Holder for cylindrical fuse
Minimum order	6 Pcs
Document ID	EO-777D45117A
Generated	2026-08-06

Product Overview

2P 10x38MFH30A1000Vdc gPV with indicator

2P 10x38MFH30A1000Vdc gPV with indicator - Fuse holder, low voltage, 32 A, DC 1000 V, 10 x 38 mm, gPV, 2P, UL, IEC, with indicator

Fuse Holder

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

EL-Nummer (Norway)4300322Fuse holder, low voltage, 32 A, DC 1000 V, 10 x 38 mm, gPV, 2P, UL, IEC, with indicatorFuse accessory, fuse-holder, low voltage, 32 A, DC 1000 V, 10 x 38 mm, gPV, 2P, UL, IEC, with indicator, DIN rail mounting, modular, colour-coded, Rated for use with 75°C or 90°C wire, fine stranded wire, spade terminals and with comb-bus bars., Use any higher temperature rated wire with appropriate derating. Photovoltaic, for cylindrical fuse-links, IEC, cULus, CCC, CSA, URDelivery program

Product rangeFuse accessoryBasic functionFuse-holderField of applicationlow voltageRated current [I]₃₂ ARated voltageDC 1000 VSize10 x 38 mmUtilization categorygPVStatus indicatorwith indicatorDescriptionDIN rail mounting colour-coded

Rated for use with 75°C or 90°C wire

fine stranded wire

spade terminals and with comb-bus bars

Use any higher temperature rated wire with appropriate derating.

ModularNumber of poles2Pusable for size/applicationsPhotovoltaic

for cylindrical fuse-linksStandard/ApprovalUL

IECStandards/RegulationsIEC

cULus

CCC

CSA

URTechnical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Holder for cylindrical fuse (EC002705)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Holder for cylindrical fuse ()

[ADI305007])Nominal voltage1500 VMounting methodDIN railFor fuse size10x38 mmNumber of poles2Concurrently

switching N-neutralNoLockableYesOptical defect indicationYesWidth in...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CHPV2IU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.