

INDUSTRIAL COMPONENT DATA

CI-K2H-T3-2 269462 Y7-269462 EATON ELECTRIC Insulated enclosure, HxWxD 181x100x100mm, for T3-2

Brand: EATON - MOELLER | Manufacturer Part Number: CI-K2H-T3-2



Manufacturer	EATON - MOELLER
MPN / Reference	CI-K2H-T3-2
Catalog number	Y7-269462
Category	Empty enclosure for switchgear
Minimum order	1 Pcs
Document ID	EO-D0B902EA6A
Generated	2026-08-06

Product Overview

Insulated enclosure, HxWxD=181x100x100mm, for T3-2

CI-K2H-T3-2

Eaton Moeller® series CI-K Insulated enclosure, HxWxD=181x100x100mm, for T3-2

Small enclosure, degree of protection IP65, glass-fiber reinforced polycarbonate, enclosure base RAL 9005, black/operator only RAL 7035, light gray, hard metric cable entry knockouts top, bottom, in the back plate, indicator light L-. can be mounted in base knock-out M20/M25, for T3-../Z switch, 1-2 contact units

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series CI-K Insulated enclosure Catalog Number 269462 Model Code CI-K2H-T3-2 EAN 4015082694623 Product Length/Depth 181 mm Product Height 84 mm Product Width 100 mm Product Weight 0.35 kg

Compliances CE Catalog Notes 1 contact unit = 2 contacts Features & Functions

Enclosure material Plastic Fitted with: Additional terminal

Metric knockouts General

Degree of protection IP65

NEMA 12 Model Surface mounting Type Insulated enclosure Used with with an additional PE clamp Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 40 °C Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 12.5 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W Radiated heat dissipation with separate mounting 12.5 W (at an ambient temperature of 20 °C) 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Meets the prod...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CI-K2H-T3-2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.