

INDUSTRIAL COMPONENT DATA

NZMH2-A100-SVE 113332 Y7-113332 EATON ELECTRIC

Circuit-breaker, 3p, 100A, plug-in module

Brand: EATON - MOELLER | Manufacturer Part Number: NZMH2-A100-SVE



Manufacturer	EATON - MOELLER
MPN / Reference	NZMH2-A100-SVE
Catalog number	Y7-113332
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-749C5134CE
Generated	2026-08-04

Product Overview

Circuit-breaker, 3p, 100A, plug-in module

NZMH2-A100-SVE

Circuit-breaker NZM2, 3 pole, Switching capacity 400/415 V 50 Hz(Icu): 150 kA, Rated current = rated uninterrupted current Rated current = rated uninterrupted current(In = Iu): 100 A, Installation type: Plug-in units, Screw connection, Standard/Approval: IEC, Protective function: System and cable protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Circuit-breaker, 3p, 100A, plug-in moduleCircuit-breaker NZM2, 3 pole, Switching capacity 400/415 V 50 Hz(Icu): 150 kA, Rated current = rated uninterrupted current Rated current = rated uninterrupted current(In = Iu): 100 A, Installation type: Plug-in units, Screw connection, Standard/Approval: IEC, Protective function: System and cable protection

General specificationsProduct nameEaton Moeller series NZM molded case circuit breaker thermo-magneticPart no.NZMH2-A100-SVEEAN4015081128679Product Length/Depth180 millimetreProduct height245 millimetreProduct width105 millimetreProduct weight2.801 kilogramCompliancesRoHS conformCertificationsIEC IEC/EN 60947Product TradenameNZMProduct TypeMolded case circuit breakerProduct Sub TypeThermo-magneticDelivery programApplicationUse in unearthed supply systems at 690 VTypeCircuit breakerCircuit breaker frame typeNZM2Accessories requiredNZM2-XSVSNumber of polesThree-poleAmperage Rating100 ARelease systemThermomagnetic releaseFeaturesMotor drive optional

Protection unitSpecial featuresMaximum back-up fuse, if the expected short-circuit currents at the installation location

exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I_{cn}) Rated current = rated uninterrupted current: 100 A Technical Data - Electrical Voltage rating 690 V - 690 V Rated insulation voltage (U_i) 1000 V AC Rated impulse withstand voltage (U_{imp}) at auxiliary contacts 6000 V Rated impulse withstand voltage (U_{imp}) at main contacts 8000 V Rate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMH2-A100-SVE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.