

INDUSTRIAL COMPONENT DATA

NZMH2-A125-FIA30-BT 129711 Y7-129711 EATON ELECTRIC Circuit-breaker, 3p, 125A, box terminals, +residual curr..

Brand: EATON - MOELLER | Manufacturer Part Number: NZMH2-A125-FIA30-BT



Manufacturer	EATON - MOELLER
MPN / Reference	NZMH2-A125-FIA30-BT
Catalog number	Y7-129711
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-2D7306FCFE
Generated	2026-08-06

Product Overview

Circuit-breaker, 3p, 125A, box terminals, +residual current circuit-breaker, 30mA, AC/DC sensitive

NZMH2-A125-FIA30-BT

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 125A, box terminals, +residual current circuit-breaker, 30mA, AC/DC sensitive

Circuit-breaker NZM2, 3 pole, Switching capacity 400/415 V 50 Hz(Icu): 150 kA, Rated current = rated uninterrupted current Rated current = rated uninterrupted current(In = Iu): 125 A, Installation type: Fixed, Box terminal, Standard/Approval: IEC, Protective function: System and cable protection, fire protection, personnel protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM molded case circuit breaker thermo-magnetic Catalog Number 129711 Model Code NZMH2-A125-FIA30-BT EAN 4015081270224 Product Length/Depth 293 mm Product Height 145 mm Product Width 140 mm Product Weight 5.58 kg Compliances RoHS conform Certifications IEC

EN 62423: Type B

VDE 0660

IEC/EN 60947 Product specifications

Type Circuit breaker Special features Application Use in unearthed supply systems at 690 V Amperage Rating 125 A

Voltage rating 400 V - 400 V Circuit breaker frame type NZM2 Features Motor drive optional

Protection unit 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMH2-A125-FIA30-BT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.