

INDUSTRIAL COMPONENT DATA

**IZMX40N3-A20W 149793 RES8203W22MNMNN2MNDX EATON
ELECTRIC Circuit-breaker, 3p, 2000 A, AF**

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX40N3-A20W



Manufacturer	EATON - MOELLER
MPN / Reference	IZMX40N3-A20W
Catalog number	RES8203W22MNMNN2MNDX
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-F6CCACB289
Generated	2026-08-05

Product Overview

Circuit-breaker, 3p, 2000 A, AF

Circuit-breaker, 3p, 2000A, withdrawable

Circuit-breaker IZMX40 (Air circuit-breakers/switch-disconnectors), 3 pole, Current Range: Up to 4000 A, Rated current = rated uninterrupted current($I_n = I_u$): 2000 A, Rated ultimate short-circuit breaking capacity up to 440V/690V 42/42(I_{cu}): 85 kA, Rated service short-circuit breaking capacity up to 440V/690V 42/42(I_{cs}): 85 kA, Overload release, min.(I_r): 1000 A, Overload release, max.(I_r): 2000 A, Installation type: Withdrawable, Standard/Approval: IEC, Protective function: System protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

General specifications

Product Name Eaton Moeller series IZMX/INX circuit-breaker Catalog Number 149793 Model Code IZMX40N3-A20W EAN 4015081463619 Product Length/Depth 584 mm Product Height 597 mm Product Width 521 mm Product Weight 69 kg

Compliances IEC/EN 60947

IEC

RoHS conform Certifications IEC Rated

EN Listed

IEC 60947

EN 60947 Delivery program

Type Frame IZMX40 Number of poles Three-pole Amperage Rating 2000 A Release system Electronic release Technical data - electrical

Voltage rating 690 V Voltage rating at AC 690 V AC Rated operating voltage (Ue) - min 690 V Rated operating voltage (Ue) - max 690 V Rated insulation voltage (Ui) 1000 V Rated impulse withstand voltage (Uimp) 12 kV AC Rated uninterrupted current (Iu) 2000 A Rated uninterrupted current (Iu) at 50°C 2000 A Rated uninterrupted current (Iu) at 60°C 2000 A Rated uninterrupted current (Iu) at 70°C 2000 A Rated short-time withstand current (t = 1 s) 85 kA Rated short-time withstand current at 50/60 Hz (t = 3 s) 66 kA Overload release current setting - min 1000 A Overload release current setting - max 2000 A Short-circuit release non-delayed setting - min 4000 A Short-circuit release non-delayed setting - max 24000 A Adjustment range short-term delayed short-circuit release - min 0 A Adjustment range short-term delayed short-circuit release - max 0 A Adjustment range undelayed short-circuit release - min 4000 A Adjustment range undelayed short-circuit release - max 24000 A Rated short-circuit breaking capacity...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX40N3-A20W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.