

INDUSTRIAL COMPONENT DATA

NZMN2-AF200-NA 269187 Y7-269187 EATON ELECTRIC

Circuit-breaker, 3p, 200A

Brand: EATON - MOELLER | Manufacturer Part Number: NZMN2-AF200-NA



Manufacturer	EATON - MOELLER
MPN / Reference	NZMN2-AF200-NA
Catalog number	Y7-269187
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-B0EAC38596
Generated	2026-08-05

Product Overview

Circuit-breaker, 3p, 200A

NZMN2-AF200-NA

Circuit-breaker NZM2, 3 pole, Switching capacity SCCR 600Y/347 V 60 Hz(Icu): 25 kA, Switching capacity SCCR 480 V 60 Hz(Icu): 35 kA, Rated current = rated uninterrupted current (In = Iu): 200 A, Installation type: Fixed, Screw connection, Standard/Approval: UL/CSA, IEC, Protective function: System and cable protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Circuit-breaker, 3p, 200A
Circuit-breaker NZM2, 3 pole, Switching capacity SCCR 600Y/347 V 60 Hz(Icu): 25 kA, Switching capacity SCCR 480 V 60 Hz(Icu): 35 kA, Rated current = rated uninterrupted current (In = Iu): 200 A, Installation type:

Fixed, Screw connection, Standard/Approval: UL/CSA, IEC, Protective function: System and cable protection

General specifications
Product name Eaton Moeller series NZM molded case circuit breaker thermo-magnetic

Part no. NZMN2-AF200-NA EAN 4015082691875 Product Length/Depth 149 millimetre Product height 195 millimetre Product

width 105 millimetre Product weight 2.399 kilogram Complies RoHS conform Certifications IEC

UL/CSA

IEC/EN 60947

UL (Category Control Number DIVQ)

CSA certified

UL listed

CSA (File No. 22086)

UL 489

CSA-C22.2 No. 5-09

CSA (Class No. 1432-01)

CE marking

IEC 60947-2

UL (File No. E31593)

Specially designed for North AmericaProduct TradenameNZMProduct TypeMolded case circuit breakerProduct Sub TypeThermo-magneticDelivery programApplicationBranch circuits, feeder circuits

Use in unearthed supply systems at 690 VTypeCircuit breakerCircuit breaker frame typeNZM2Number of

polesThree-poleAmperage Rating200 ARelease systemThermomagnetic releaseFeaturesProtection unit

Motor drive optionalSpecial featuresMaximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn)

Rated current = rated uninterrupted current: 200 A

Swit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMN2-AF200-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.