

INDUSTRIAL COMPONENT DATA

NZMH2-M200 281309 Y7-281309 EATON ELECTRIC

Circuit-breaker, 3p, 200A

Brand: EATON - MOELLER | Manufacturer Part Number: NZMH2-M200



Manufacturer	EATON - MOELLER
MPN / Reference	NZMH2-M200
Catalog number	Y7-281309
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-7F2A71BC32
Generated	2026-08-05

Product Overview

Circuit-breaker, 3p, 200A

NZMH2-M200

Circuit-breakers of the NZM...M series cover all applications with only four compact sizes and are suitable for the IEC market. The mounting is always flexible due to the modular function groups. With thermomagnetic release for the motor protection. Notes: tripping class 10A, IEC/EN 60947-4-1, IEC/EN 60947-2 circuit-breakers fulfill all requirements of the switching category AC-3.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Circuit-breaker, 3p, 200A Circuit-breakers of the NZM...M series cover all applications with only four compact sizes and are suitable for the IEC market. The mounting is always flexible due to the modular function groups. With thermomagnetic release for the motor protection. Notes: tripping class 10A, IEC/EN 60947-4-1, IEC/EN 60947-2 circuit-breakers fulfill all requirements of the switching category AC-3.

General specifications
Product name Eaton Moeller series NZM molded case circuit breaker thermo-magnetic
Part no. NZMH2-M200
EAN 4015082813093
Product Length/Depth 149 millimetre
Product height 184 millimetre
Product width 105 millimetre
Product weight 2.34 kilogram
Compliance RoHS conform
Certifications IEC/EN 60947
IEC
Product Tradename NZM
Product Type Molded case circuit breaker
Product Sub Type Thermo-magnetic
Delivery program Application Use in unearthed supply systems at 690 V
Type Circuit breaker
Circuit breaker frame type NZM2
Number of poles Three-pole
Amperage Rating 200 A
Release system Thermomagnetic release
Special features Maximum back-up fuse,

if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I_{cn})

Rated current = rated uninterrupted current: 200 A

Tripping class 10 A

IEC/EN 60947-4-1, IEC/EN 60947-2

The circuit-breaker fulfills all requirements for AC-3 switching category. Fitted with: Thermal protection
Technical Data -
Electrical Voltage rating 690 V - 690 V Rated insulation voltage (U_i) 1000...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMH2-M200 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.