

INDUSTRIAL COMPONENT DATA

NZMC1-A25-SVE 112754 Y7-112754 EATON ELECTRIC

Circuit-breaker, 3p, 25A, plug-in module

Brand: EATON - MOELLER | Manufacturer Part Number: NZMC1-A25-SVE



Manufacturer	EATON - MOELLER
MPN / Reference	NZMC1-A25-SVE
Catalog number	Y7-112754
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-84B0201907
Generated	2026-08-02

Product Overview

Circuit-breaker, 3p, 25A, plug-in module

NZMC1-A25-SVE

Circuit-breaker NZM1, 3 pole, Switching capacity 400/415 V 50 Hz(Icu): 36 kA, Rated current = rated uninterrupted current
Rated current = rated uninterrupted current(In = Iu): 25 A, Installation type: Plug-in units, Box terminal, Standard/Approval:
IEC, Protective function: System and cable protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Circuit-breaker, 3p, 25A, plug-in module
Circuit-breaker NZM1, 3 pole, Switching capacity 400/415 V 50 Hz(Icu): 36 kA,
Rated current = rated uninterrupted current
Rated current = rated uninterrupted current(In = Iu): 25 A, Installation type:
Plug-in units, Box terminal, Standard/Approval: IEC, Protective function: System and cable protection
General specifications
Product name Eaton Moeller series NZM molded case circuit breaker thermo-magnetic
Part no. NZMC1-A25-SVE
EAN 4015081122943
Product Length/Depth 90 millimetre
Product height 201 millimetre
Product width 95 millimetre
Product weight 1.227 kilogram
Compliance RoHS conform
Certifications IEC
IEC/EN 60947
Product Tradename NZM
Product Type Molded case circuit breaker
Product Sub Type Thermo-magnetic
Delivery program Application Use in unearthed supply systems at 690 V
Type Circuit breaker
Circuit breaker frame type NZM1
Accessories required NZM1-XSVS
Number of poles Three-pole
Amperage Rating 25 A
Release system Thermomagnetic release
Features Protection unit
Special features Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity

Icn)

Rated current = rated uninterrupted current: 25 A

Terminal capacity hint: Up to 95 mm² can be connected depending on the cable manufacturer. Technical Data -

Electrical Voltage rating 690 V - 690 V Rated insulation voltage (Ui) 690 V AC Rated impulse withstand voltage (Uimp) at auxiliary contacts 6000 V Rated i...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMC1-A25-SVE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.