

INDUSTRIAL COMPONENT DATA

IZMX40H3-A32F 149731 RESC323B22QNMNN2MN1X EATON ELECTRIC Circuit-breaker, 3p, 3200 A, fixed

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX40H3-A32F



Manufacturer	EATON - MOELLER
MPN / Reference	IZMX40H3-A32F
Catalog number	RESC323B22QNMNN2MN1X
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-7B1DCEF46E
Generated	2026-08-05

Product Overview

Circuit-breaker, 3p, 3200 A, fixed

Circuit-breaker IZMX40 (Air circuit-breakers/switch-disconnectors), 3 pole, Current Range: Up to 4000 A, Rated current = rated uninterrupted current($I_n = I_u$): 3200 A, Rated ultimate short-circuit breaking capacity up to 440V/690V 42/42(I_{cu}): 105 kA, Rated service short-circuit breaking capacity up to 440V/690V 42/42(I_{cs}): 105 kA, Overload release, min.(I_r): 1600 A, Overload release, max.(I_r): 3200 A, Installation type: Fixed, Standard/Approval: IEC, Protective function: System protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Circuit-breaker, 3p, 3200A, fixedCircuit-breaker IZMX40 (Air circuit-breakers/switch-disconnectors), 3 pole, Current Range: Up to 4000 A, Rated current = rated uninterrupted current($I_n = I_u$): 3200 A, Rated ultimate short-circuit breaking capacity up to 440V/690V 42/42(I_{cu}): 105 kA, Rated service short-circuit breaking capacity up to 440V/690V 42/42(I_{cs}): 105 kA, Overload release, min.(I_r): 1600 A, Overload release, max.(I_r): 3200 A, Installation type: Fixed, Standard/Approval: IEC, Protective function: System protectionDelivery program

Product rangeAir circuit-breakers/switch-disconnectorsProduct rangeOpen circuit-breakersCurrent RangeUp to 4000 AProtective functionSystem protectionInstallation typeFixedConstruction sizeIZMX40Release systemElectronic releaseStandard/ApprovalIECNumber of poles3 poleDegree of ProtectionIP20, IP55 with protective cover, IP41 door sealing frameoptionally fittable by user with comprehensive accessoriesRated current = rated uninterrupted current [$I_n = I_u$]3200 ARated ultimate short-circuit breaking capacity up to 440V/690V 42/42 [I_{cu}]105 kARated service short-circuit breaking capacity up to 440V/690V 42/42 [I_{cs}]105 kAOverload release, min. [I_r]1600 AOverload release, max. [I_r]3200

ANon-delayed[li= Inx ...]2 - 12NotesMain terminals must be separately ordered.

Technical data

GeneralStandardsIEC/EN 60947Ambient temperatureStorage [?]-40 - +70 °CAmbient temperatureOperating (open)-25 - +70 °CMounting positionUtilization categoryBDEgree of Protection...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX40H3-A32F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.