

INDUSTRIAL COMPONENT DATA

NZMB2-A32-NA 269208 Y7-269208 EATON ELECTRIC

Circuit-breaker, 3p, 32A

Brand: EATON - MOELLER | Manufacturer Part Number: NZMB2-A32-NA



Manufacturer	EATON - MOELLER
MPN / Reference	NZMB2-A32-NA
Catalog number	Y7-269208
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-460E54C448
Generated	2026-08-05

Product Overview

Circuit-breaker, 3p, 32A

NZMB2-A32-NA

Circuit-breaker NZM2, 3 pole, Switching capacity SCCR 480Y/277 V 60 Hz(Icu): 25 kA, Switching capacity SCCR 600Y/347 V 60 Hz(Icu): 18 kA, Switching capacity SCCR 480 V 60 Hz(Icu): 25 kA, Rated current = rated uninterrupted current (In = Iu): 32 A, Installation type: Fixed, Screw connection, Standard/Approval: UL/CSA, IEC, Protective function: System and cable protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

Additional Product Information

Circuit-breaker, 3p, 32ACircuit-breaker NZM2, 3 pole, Switching capacity SCCR 480Y/277 V 60 Hz(Icu): 25 kA, Switching capacity SCCR 600Y/347 V 60 Hz(Icu): 18 kA, Switching capacity SCCR 480 V 60 Hz(Icu): 25 kA, Rated current = rated uninterrupted current (In = Iu): 32 A, Installation type: Fixed, Screw connection, Standard/Approval: UL/CSA, IEC, Protective function: System and cable protection

General specificationsProduct nameEaton Moeller series NZM molded case circuit breaker thermo-magneticPart no.NZMB2-A32-NAEAN4015082692087Product Length/Depth149 millimetreProduct height195 millimetreProduct width105 millimetreProduct weight2.409 kilogramCompliancesRoHS conformCertificationsIEC

UL listed

UL 489

IEC 60947-2

UL (Category Control Number DIVQ)

IEC/EN 60947

CSA (File No. 22086)

UL (File No. E31593)

CSA (Class No. 1432-01)

Specially designed for North America

CSA certified

CE marking

UL/CSA

CSA-C22.2 No. 5-09Product TradenameNZMProduct TypeMolded case circuit breakerProduct Sub

TypeThermo-magneticDelivery programApplicationBranch circuits, feeder circuitsUse in unearthed supply systems at 440

VTypeCircuit breakerCircuit breaker frame typeNZM2Number of polesThree-poleAmperage Rating32 ARelease

systemThermomagnetic releaseFeaturesProtection unit

Motor drive optionalSpecial featuresMaximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn)Rated....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMB2-A32-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.