

INDUSTRIAL COMPONENT DATA

NZMN1-M40 265718 Y7-265718 EATON ELECTRIC

Circuit-breaker, 3p, 40A

Brand: EATON - MOELLER | Manufacturer Part Number: NZMN1-M40



Manufacturer	EATON - MOELLER
MPN / Reference	NZMN1-M40
Catalog number	Y7-265718
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-F356DE5A14
Generated	2026-08-03

Product Overview

Circuit-breaker, 3p, 40A

NZMN1-M40

Series NZM...M circuit-breakers cover all application cases with just four compact sizes and are suitable for the IEC market. Modular function groups always make mounting flexible. With thermomagnetic releases for motor protection. Notes: With phase-failure sensitivity, tripping class 10A, IEC/EN 60947-4-1, IEC/EN 60947-2 circuit-breakers fulfill all requirements of the switching category AC-3.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

Circuit-breaker, 3p, 40A Series NZM...M circuit-breakers cover all application cases with just four compact sizes and are suitable for the IEC market. Modular function groups always make mounting flexible. With thermomagnetic releases for motor protection. Notes: With phase-failure sensitivity, tripping class 10A, IEC/EN 60947-4-1, IEC/EN 60947-2 circuit-breakers fulfill all requirements of the switching category AC-3.

General specifications
Product name Eaton Moeller series NZM molded case circuit breaker thermo-magnetic
Part no. NZMN1-M40
EAN 4015082657185
Product Length/Depth 88 millimetre
Product height 145 millimetre
Product width 90 millimetre
Product weight 1.032 kilogram
Compliance RoHS conform
Certifications IEC

IEC/EN 60947
Product Tradename NZM
Product Type Molded case circuit breaker
Product Sub

Type Thermo-magnetic
Delivery program Application Use in unearthed supply systems at 690 V
Type Circuit breaker
Circuit breaker frame type NZM1
Number of poles Three-pole
Amperage Rating 40 A
Release system Thermomagnetic release
Special

featuresMaximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn)

Rated current = rated uninterrupted current: 40 A

Terminal capacity hint: Up to 95 mm² can be connected depending on the cable manufacturer.

With phase-failure sensitivity

Tripping class 10 A

IEC/EN 60947-4-1, IEC/EN 60947-2

The circuit-breaker fulfills all requirements for AC-3 switc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMN1-M40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.