

INDUSTRIAL COMPONENT DATA

NZMB1-S40-SVE 112724 Y7-112724 EATON ELECTRIC

Circuit-breaker, 3p, 40A, plug-in module

Brand: EATON - MOELLER | Manufacturer Part Number: NZMB1-S40-SVE



Manufacturer	EATON - MOELLER
MPN / Reference	NZMB1-S40-SVE
Catalog number	Y7-112724
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-4CE10BF8F8
Generated	2026-08-04

Product Overview

Circuit-breaker, 3p, 40A, plug-in module

NZMB1-S40-SVE

Series NZM...S circuit-breakers cover all application cases with just four compact sizes and are suitable for the IEC market. Modular function groups always make mounting flexible. With magnetic short-circuit release in connection with overload relay. With short-circuit release without overload trip. Notes: circuit-breakers fulfill all requirements of the switching category AC-3.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Circuit-breaker, 3p, 40A, plug-in moduleSeries NZM...S circuit-breakers cover all application cases with just four compact sizes and are suitable for the IEC market. Modular function groups always make mounting flexible. With magnetic short-circuit release in connection with overload relay. With short-circuit release without overload trip. Notes: circuit-breakers fulfill all requirements of the switching category AC-3.

General specificationsProduct nameEaton Moeller series NZM molded case circuit breaker magneticPart no.NZMB1-S40-SVEEAN4015081122646Product Length/Depth90 millimetreProduct height201 millimetreProduct width95 millimetreProduct weight1.2 kilogramCompliancesRoHS conformCertificationsIEC/EN 60947 IECProduct TradenameNZMProduct TypeMolded case circuit breakerProduct Sub TypeMagneticDelivery programApplicationUse in unearthed supply systems at 440 VTypeCircuit breakerCircuit breaker frame typeNZM1Accessories requiredNZM1-XSVSNumber of polesThree-poleAmperage Rating40 ARelease

system Thermomagnetic release Special features Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I_{cn})

Motor protection in conjunction with overload relay

With short-circuit release

Without overload release I_r

IEC/EN 60947-4-1, IEC/EN 60947-2

The circuit-breaker fulfills all requirements for AC-3 switching category.

Rated current = rated uninterrupted current: 40 A

Te...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMB1-S40-SVE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.