

INDUSTRIAL COMPONENT DATA

NZMN2-A63-NA 269222 Y7-269222 EATON ELECTRIC

Circuit-breaker, 3p, 63A

Brand: EATON - MOELLER | Manufacturer Part Number: NZMN2-A63-NA



Manufacturer	EATON - MOELLER
MPN / Reference	NZMN2-A63-NA
Catalog number	Y7-269222
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-C92D26893F
Generated	2026-08-03

Product Overview

Circuit-breaker, 3p, 63A

NZMN2-A63-NA

Circuit-breaker NZM2, 3 pole, Switching capacity SCCR 600Y/347 V 60 Hz(Icu): 25 kA, Switching capacity SCCR 480 V 60 Hz(Icu): 35 kA, Rated current = rated uninterrupted current (In = Iu): 63 A, Installation type: Fixed, Screw connection, Standard/Approval: UL/CSA, IEC, Protective function: System and cable protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

Additional Product Information

Circuit-breaker, 3p, 63A
Circuit-breaker NZM2, 3 pole, Switching capacity SCCR 600Y/347 V 60 Hz(Icu): 25 kA, Switching capacity SCCR 480 V 60 Hz(Icu): 35 kA, Rated current = rated uninterrupted current (In = Iu): 63 A, Installation type: Fixed, Screw connection, Standard/Approval: UL/CSA, IEC, Protective function: System and cable protection
General specifications
Product name Eaton Moeller series NZM molded case circuit breaker thermo-magnetic
Part no. NZMN2-A63-NA
EAN 4015082692223
Product Length/Depth 149 millimetre
Product height 195 millimetre
Product width 105 millimetre
Product weight 2.417 kilogram
Compliances RoHS conform
Certifications IEC 60947-2

CE marking

UL/CSA

Specially designed for North America

UL 489

CSA-C22.2 No. 5-09

UL listed

IEC/EN 60947

UL (Category Control Number DIVQ)

UL (File No. E31593)

CSA certified

CSA (Class No. 1432-01)

CSA (File No. 22086)

IEC Product Tradename NZM Product Type Molded case circuit breaker Product Sub Type Thermo-magnetic Delivery program Application Branch circuits, feeder circuits

Use in unearthed supply systems at 690 V Type Circuit breaker Circuit breaker frame type NZM2 Number of

poles Three-pole Amperage Rating 63 A Release system Thermomagnetic release Features Protection unit

Motor drive optional Special features Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I_{cn})

Rated current = rated uninterrupted current: 63 A

Switches c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMN2-A63-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.