

INDUSTRIAL COMPONENT DATA

NZMN4-AEF700-NA 271109 Y7-271109 EATON ELECTRIC

Circuit-breaker, 3p, 700A

Brand: EATON - MOELLER | Manufacturer Part Number: NZMN4-AEF700-NA



Manufacturer	EATON - MOELLER
MPN / Reference	NZMN4-AEF700-NA
Catalog number	Y7-271109
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-BA7E6A9076
Generated	2026-08-05

Product Overview

Circuit-breaker, 3p, 700A
Int. Auto NZM, 3P, 700A, NA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

Circuit-breaker, 3p, 700ACircuit-breaker NZM4, 3 pole, Switching capacity SCCR 480Y/277 V 60 Hz(Icu): 100 kA, Switching capacity SCCR 480 V 60 Hz(Icu): 42 kA, Rated current = rated uninterrupted current (In = Iu): 700 A, Installation type: Fixed, Screw connection, Standard/Approval: UL/CSA, IEC, Protective function: System and cable protection

General specificationsProduct nameEaton Moeller series NZM molded case circuit breaker electronicPart no.NZMN4-AEF700-NAEAN4015082711092Product Length/Depth401 millimetreProduct height207 millimetreProduct width210 millimetreProduct weight21 kilogramCompliancesRoHS conformCertificationsIEC 60947-2

UL 489

CSA certified

Specially designed for North America

IEC/EN 60947

CSA-C22.2 No. 5-09

UL listed

UL (File No. E31593)

CE marking

CSA (File No. 22086)

CSA (Class No. 1432-01)

UL (Category Control Number DIVQ)

IEC

UL/CSA Product Trade Name NZM Product Type Molded case circuit breaker Product Sub Type Electronic Delivery

program Application Branch circuits, feeder circuits Use in unearthed supply systems at 525 V Type Circuit breaker Circuit

breaker frame type NZM4 Number of poles Three-pole Amperage Rating 700 A Release system Electronic

release Features Protection unit

Motor drive optional Special features For AC-3 rated operational current with NZM4 the following applies: 400 V: max. 650 kW; 690 V: max. 600 kW (switching capacity, rated making and breaking capacity) Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMN4-AEF700-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.