

INDUSTRIAL COMPONENT DATA

NZMN4-VEF700-NA 271137 Y7-271137 EATON ELECTRIC

Circuit-breaker, 3p, 700A

Brand: EATON - MOELLER | Manufacturer Part Number: NZMN4-VEF700-NA



Manufacturer	EATON - MOELLER
MPN / Reference	NZMN4-VEF700-NA
Catalog number	Y7-271137
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-15BF28AAF6
Generated	2026-08-06

Product Overview

Circuit-breaker, 3p, 700A
Int. Auto NZM, 3P, 700A, NA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

Circuit-breaker, 3p, 700A
Circuit-breaker NZM4, 3 pole, Switching capacity SCCR 480 V 60 Hz(Icu): 42 kA, Switching capacity SCCR 600 V 60 Hz(Icu): 35 kA, Rated current = rated uninterrupted current Rated current = rated uninterrupted current(I_n = I_u): 700 A, Installation type: Fixed, Screw connection, Standard/Approval: UL/CSA, IEC, Protective function: Systems, cable, selectivity and generator protection

General specifications
Product name Eaton Moeller series NZM - Molded Case Circuit Breaker

Part no. NZMN4-VEF700-NA EAN4015082711375
Product Length/Depth 401 millimetre
Product height 207 millimetre
Product width 210 millimetre
Product weight 21 kilogram

Compliances RoHS conform
Certifications CSA (File No. 22086)

CSA (Class No. 1432-01)

CE marking

CSA-C22.2 No. 5-09

CSA certified

UL (File No. E31593)

UL listed

IEC/EN 60947

UL/CSA

UL 489

Specially designed for North America

UL (Category Control Number DIVQ)

IEC

IEC 60947-2Product TradenameNZMProduct TypeMolded Case Circuit BreakerProduct Sub TypeNoneDelivery programApplicationBranch circuits, feeder circuitsUse in unearthed supply systems at 525 VTypeCircuit breakerCircuit breaker frame typeNZM4Number of polesThree-poleAmperage Rating700 ARelease systemElectronic releaseFeaturesProtection unit

Motor drive optionalSpecial featuresFor AC-3 rated operational current with NZM4 the following applies: 400 V: max. 650 kW; 690 V: max. 600 kW (switching capacity, rated making and breaking capacity)Maximum back-up fuse, if the expected short-circui...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMN4-VEF700-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.