

INDUSTRIAL COMPONENT DATA

NZMN4-AEF900-NA 271111 Y7-271111 EATON ELECTRIC

Circuit-breaker, 3p, 900A

Brand: EATON - MOELLER | Manufacturer Part Number: NZMN4-AEF900-NA



Manufacturer	EATON - MOELLER
MPN / Reference	NZMN4-AEF900-NA
Catalog number	Y7-271111
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-5B337F2850
Generated	2026-08-04

Product Overview

Circuit-breaker, 3p, 900A

Int. Auto NZM, 3P, 900A, NA

Circuit-breaker NZM4, 3 pole, Switching capacity SCCR 480Y/277 V 60 Hz(Icu): 100 kA, Switching capacity SCCR 480 V 60 Hz(Icu): 42 kA, Rated current = rated uninterrupted current (In = Iu): 900 A, Installation type: Fixed, Screw connection, Standard/Approval: UL/CSA, IEC, Protective function: System and cable protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

Additional Product Information

Circuit-breaker, 3p, 900A
Circuit-breaker NZM4, 3 pole, Switching capacity SCCR 480Y/277 V 60 Hz(Icu): 100 kA, Switching capacity SCCR 480 V 60 Hz(Icu): 42 kA, Rated current = rated uninterrupted current (In = Iu): 900 A, Installation type: Fixed, Screw connection, Standard/Approval: UL/CSA, IEC, Protective function: System and cable protection

General specifications
Product name Eaton Moeller series NZM molded case circuit breaker electronic
Part no. NZMN4-AEF900-NA
EAN 4015082711115
Product Length/Depth 401 millimetre
Product height 207 millimetre
Product width 210 millimetre
Product weight 21 kilogram
Compliances RoHS conform
Certifications IEC 60947-2

CSA (Class No. 1432-01)

IEC/EN 60947

CE marking

UL (Category Control Number DIVQ)

UL 489

UL listed

Specially designed for North America

CSA certified

CSA (File No. 22086)

UL/CSA

UL (File No. E31593)

CSA-C22.2 No. 5-09

IEC Product Type Molded case circuit breaker Product Sub Type Electronic Delivery

program Application Branch circuits, feeder circuits Use in unearthed supply systems at 525 V Type Circuit breaker Circuit

breaker frame type NZM4 Number of poles Three-pole Amperage Rating 900 A Release system Electronic

release Features Motor drive optional

Protection unit Special features For AC-3 rated operational current with NZM4 the following applies: 400 V: max. 650 kW;

690 V: max. 600 kW (switching capacity, rated making and breaking capacity) Maximum back-up fuse, if the expected

short-circuit currents at the installation location exceed...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMN4-AEF900-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.