

INDUSTRIAL COMPONENT DATA

IZMX40B4-A10W 149950 RES6104W22-NMNN2MNDX EATON ELECTRIC Circuit-breaker, 4p, 1000 A, AF

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX40B4-A10W



Manufacturer	EATON - MOELLER
MPN / Reference	IZMX40B4-A10W
Catalog number	RES6104W22-NMNN2MNDX
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-C56B2EBF11
Generated	2026-08-04

Product Overview

Circuit-breaker, 4p, 1000 A, AF

Circuit-breaker, 4p, 1000A, withdrawable

Circuit-breaker IZMX40 (Air circuit-breakers/switch-disconnectors), 4 pole, Current Range: Up to 4000 A, Rated current = rated uninterrupted current($I_n = I_u$): 1000 A, Rated ultimate short-circuit breaking capacity up to 440V/690V 42/42(I_{cu}): 66 kA, Rated service short-circuit breaking capacity up to 440V/690V 42/42(I_{cs}): 66 kA, Overload release, min.(I_r): 500 A, Overload release, max.(I_r): 1000 A, Installation type: Withdrawable, Standard/Approval: IEC, Protective function: System protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

General specifications

Product Name Eaton Moeller series IZMX/INX circuit-breaker Catalog Number 149950 Model Code IZMX40B4-A10W EAN 4015081462049 Product Length/Depth 584 mm Product Height 597 mm Product Width 521 mm Product Weight 86 kg

Compliances IEC

IEC/EN 60947 Delivery program

Type Frame IZMX40 Number of poles Four-pole Amperage Rating 1000 A Release system Electronic release Technical data - electrical

Voltage rating at AC 690 V AC Rated operating voltage (Ue) - min 690 V Rated operating voltage (Ue) - max 690 V Rated insulation voltage (Ui) 1000 V Rated impulse withstand voltage (Uimp) 12 kV AC Rated uninterrupted current (Iu) 1000 A

Rated uninterrupted current (I_u) at 50°C 1000 A Rated uninterrupted current (I_u) at 60°C 1000 A Rated uninterrupted current (I_u) at 70°C 1000 A Rated short-time withstand current (t = 1 s) 66 kA Rated short-time withstand current at 50/60 Hz (t = 3 s) 53 kA Overload release current setting - min 500 A Overload release current setting - max 1000 A Short-circuit release non-delayed setting - min 2000 A Short-circuit release non-delayed setting - max 12000 A Adjustment range short-term delayed short-circuit release - min 0 A Adjustment range short-term delayed short-circuit release - max 0 A Adjustment range undelayed short-circuit release - min 2000 A Adjustment range undelayed short-circuit release - max 12000 A Rated short-circuit breaking capacity at 400 V, 50 Hz 66 kA Rated short-circuit making capacity up to 440 V, 50/60 Hz 145 kA Ra...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX40B4-A10W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.