

## INDUSTRIAL COMPONENT DATA

# NZMB2-4-A200 265852 Y7-265852 EATON ELECTRIC

## Circuit-breaker, 4p, 200A

Brand: EATON - MOELLER | Manufacturer Part Number: NZMB2-4-A200



|                 |                                                                   |
|-----------------|-------------------------------------------------------------------|
| Manufacturer    | EATON - MOELLER                                                   |
| MPN / Reference | NZMB2-4-A200                                                      |
| Catalog number  | Y7-265852                                                         |
| Category        | Power circuit-breaker for trafo/generator/installation protection |
| Minimum order   | 1 unit                                                            |
| Document ID     | EO-4F06256BAD                                                     |
| Generated       | 2026-08-05                                                        |

### Product Overview

Circuit-breaker, 4p, 200A

NZMB2-4-A200

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 4p, 200A, B2-4-A200

Circuit-breaker NZM2, 4 pole, Switching capacity 400/415 V 50 Hz( Icu ): 25 kA, Rated current = rated uninterrupted current

Rated current = rated uninterrupted current( In = Iu ): 200 A, Installation type: Fixed, Screw connection, Standard/Approval:

IEC, Protective function: System and cable protection

## STRUCTURED PRODUCT DATA

### Technical Specifications

| TECHNICAL ATTRIBUTE                                                  | VALUE                                    |
|----------------------------------------------------------------------|------------------------------------------|
| Rated permanent current Iu (EF001389)                                | 200 A                                    |
| Rated voltage (EF003977)                                             | 440 V                                    |
| Rated short-circuit breaking capacity Icu at 400 V, 50 Hz (EF007048) | 25 kA                                    |
| Overload release current setting (EF002336)                          | 160 A                                    |
| Adjustment range short-term delayed short-circuit release (EF007129) | 0 A                                      |
| Adjustment range undelayed short-circuit release (EF007131)          | 6 A                                      |
| Device construction (EF008240)                                       | Built-in device fixed built-in technique |
| Integrated earth fault protection (EF007296)                         | No                                       |
| Type of electrical connection of main circuit (EF006819)             | Screw connection                         |
| Suitable for DIN rail (top hat rail) mounting (EF007250)             | No                                       |
| DIN rail (top hat rail) mounting optional (EF008904)                 | Yes                                      |
| Number of auxiliary contacts as normally closed contact (EF001377)   | 0                                        |

**CONTINUED**

## Technical Specifications

| TECHNICAL ATTRIBUTE                                              | VALUE        |
|------------------------------------------------------------------|--------------|
| Number of auxiliary contacts as normally open contact (EF001376) | 0            |
| Number of auxiliary contacts as change-over contact (EF003531)   | 0            |
| With switched-off indicator (EF007006)                           | No           |
| With integrated under voltage release (EF001390)                 | No           |
| Number of poles (EF001391)                                       | 4            |
| Position of connection for main current circuit (EF006671)       | Front        |
| Type of control element (EF006976)                               | Rocker lever |
| Complete device with protection unit (EF008906)                  | Yes          |
| Motor drive integrated (EF006697)                                | No           |
| Motor drive optional (EF007386)                                  | Yes          |
| Degree of protection (IP) (EF005474)                             | IP20         |

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | EATON - MOELLER > Circuit Breakers NZM |
|--------------|----------------------------------------|

## Additional Product Information

### General specifications

Product Name Eaton Moeller series NZM molded case circuit breaker thermo-magnetic Catalog Number 265852 Model Code NZMB2-4-A200 EAN 4015082658526 Product Length/Depth 149 mm Product Height 184 mm Product Width 140 mm Product Weight 3 kg Compliances RoHS conform Certifications IEC/EN 60947

### IEC Product specifications

Type Circuit breaker Special features Application Use in unearthed supply systems at 440 V Amperage Rating 200 A Voltage rating 440 V - 440 V Circuit breaker frame type NZM2 Features Motor drive optional

Protection unit 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMB2-4-A200 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.