

INDUSTRIAL COMPONENT DATA

NZMH3-4-AE630/400-T-AVE 113587 Y7-113587 EATON ELECTRIC Circuit-breaker, 4p, 630A, 400A in 4th pole, withdra..

Brand: EATON - MOELLER | Manufacturer Part Number: NZMH3-4-AE630/400-T-AVE



Manufacturer	EATON - MOELLER
MPN / Reference	NZMH3-4-AE630/400-T-AVE
Catalog number	Y7-113587
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-67E303B3FF
Generated	2026-08-04

Product Overview

Circuit-breaker, 4p, 630A, 400A in 4th pole, withdrawable unit
NZMH3-4-AE630/400-T-AVE

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

Additional Product Information

Circuit-breaker, 4p, 630A, 400A in 4th pole, withdrawable unit Circuit-breaker NZM3, 4 pole, Switching capacity 400/415 V 50 Hz(Icu): 150 kA, Rated current = rated uninterrupted current Rated current = rated uninterrupted current(In = Iu): 630 A, Installation type: Withdrawable, Screw connection, Standard/Approval: IEC, Protective function: System and cable protection [Delivery program

Product range Circuit-breaker Protective function System and cable protection Standard/Approval IEC Installation type Withdrawable Release system Electronic release Construction size NZM3 Description Set value in neutral conductor is synchronous with set value Ir of main pole.

R.m.s. value measurement and "thermal memory"

Earth-fault release: Not dependent on mains and control voltages

Ig = 0.35 - 0.4 - 0.5 - 0.6 - 0.7 - 0.8 - 0.9 - 1.0 x In

tg = 0 - 20 - 60 - 100 - 200 - 300 - 500 - 750 - 1000 ms Number of poles 4 pole Standard equipment Screw connection

Switching capacity 400/415 V 50 Hz [Icu] 150 kA Rated current = rated uninterrupted current [In= Iu] Rated current = rated

uninterrupted current [In= lu] 630 A Neutral conductor [% of phase conductor] 60 CSA Reduced neutral conductor protection 400 A Neutral conductor protection Reduced neutral conductor protection Setting range Overload trip[Ir] 315 - 630 A Overload tripMain pole [Ir] 200 - 400 A Short-circuit releases [Irm]Non-delayed [li= Inx ...] 2 - 8 , Technical data General Standards IEC/EN 60947 Protection against direct contact Fi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMH3-4-AE630/400-T-AVE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.