

INDUSTRIAL COMPONENT DATA

NZMH3-4-VE630 265966 Y7-265966 EATON ELECTRIC

Circuit-breaker, 4p, 630A

Brand: EATON - MOELLER | Manufacturer Part Number: NZMH3-4-VE630



Manufacturer	EATON - MOELLER
MPN / Reference	NZMH3-4-VE630
Catalog number	Y7-265966
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-0C183DC16E
Generated	2026-08-06

Product Overview

Circuit-breaker, 4p, 630A

NZMH3-4-VE630

Circuit-breaker NZM3, 4 pole, Switching capacity 400/415 V 50 Hz(Icu): 150 kA, Rated current = rated uninterrupted current Rated current = rated uninterrupted current(In = Iu): 630 A, Installation type: Fixed, Screw connection, Standard/Approval: IEC, Protective function: Systems, cable, selectivity and generator protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Circuit-breaker, 4p, 630A
Circuit-breaker NZM3, 4 pole, Switching capacity 400/415 V 50 Hz(Icu): 150 kA, Rated current = rated uninterrupted current Rated current = rated uninterrupted current(In = Iu): 630 A, Installation type: Fixed, Screw connection, Standard/Approval: IEC, Protective function: Systems, cable, selectivity and generator protection
General specifications
Product name Eaton Moeller series NZM molded case circuit breaker electronic
Part no. NZMH3-4-VE630
EAN 4015082659660
Product Length/Depth 166 millimetre
Product height 275 millimetre
Product width 185 millimetre
Product weight 8.4 kilogram
Compliance RoHS conform
Certifications IEC/EN 60947
IEC
Product Tradename NZM
Product Type Molded case circuit breaker
Product Sub Type Electronic
Delivery program
Application Use in unearthed supply systems at 690 V
Type Circuit breaker
Circuit breaker frame type NZM3
Number of poles Four-pole
Amperage Rating 630 A
Release system Electronic release
Features Motor drive optional
Protection unit
Special features Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn)
R.m.s. value measurement

and "thermal memory" Adjustable time delay setting to overcome current peaks t_r at $6 \times I_r$ also infinity (without overload releases) Adjustable delay time t_{sd} t constant function: switchable Rated current = rated uninterrupted current: 630 A Terminal capacity hint: Up to 240 mm² can be connected d...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMH3-4-VE630 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.