

INDUSTRIAL COMPONENT DATA

PKZ0-XHT-MCC 164297 Y7-164297 EATON ELECTRIC Industrial Automation Bussines and Industrial Control Devices I..

Brand: EATON - MOELLER | Manufacturer Part Number: PKZ0-XHT-MCC



Manufacturer	EATON - MOELLER
MPN / Reference	PKZ0-XHT-MCC
Catalog number	Y7-164297
Category	Door coupling handle for switchgear
Minimum order	1 Pcs
Document ID	EO-A1043B6CE4
Generated	2026-08-02

Product Overview

Industrial Automation Bussines and Industrial Control Devices IEC Starters and Contactors

PKZ0-XHT-MCC

Eaton Moeller® series PKZ0 Door coupling handle, for MCC-V. 90 degree, twisted

For use as a main switch to EN 60204 in MCC power distribution systems and with PKZM0 installed when rotated by 90°

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZ0 Accessory Door coupling handle Catalog Number 164297 Model Code

PKZ0-XHT-MCC EAN 4015081608256 Product Length/Depth 235 mm Product Height 66 mm Product Width 64 mm

Product Weight 0.16 kg Certifications EN 60204 Catalog Notes Cannot be used in combination with VHI20-PKZ0. Features

& Functions

Color Black Features Lockable Fitted with: Axis extension

Door interlock

ON/OFF switch position and "+" (tripped), lockable

3 padlocks, 4 - 8 mm hasp thickness General

Product Category Accessories Suitable as Main switch to EN 60204 in MCC power distribution systems and with PKZM0

installed when rotated by 90° Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,

current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation,

non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance

of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal

heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resist...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKZO-XHT-MCC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.