

INDUSTRIAL COMPONENT DATA

IZMX-SR230AD 123742 0004357981 EATON ELECTRIC Closing release 220-240 VAC/DC

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX-SR230AD



Manufacturer	EATON - MOELLER
MPN / Reference	IZMX-SR230AD
Catalog number	0004357981
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-B4C5B24138
Generated	2026-08-01

Product Overview

Closing release 220-240 VAC/DC

IZMX-SR230AD

Suitable for remote switching on

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

Additional Product Information

Closing release 220-240 VAC/DC EL-Nummer (Norway) 0004357981 Suitable for remote switching on [Delivery program Product range Accessories Accessories Remote switching Accessories closing release Without latch check switch.

Maximum operating frequency [Actuations/minute] 3 Limited to 3/min due to the high pick-up current for 35 ms.

Please note - the circuit-breaker's switching frequency = 60/h Rated control voltage [Us] 208 - 240 V AC 50/60 Hz

208 - 250 V DC V Operating range [x US] 0,85 - 1,1 Factor max. pick-up current (35ms) [In] 2.89 A max. pull-in power (35ms) [AC/DC] 500 VA/W Circuit-breaker total switching time [@ US=100%] 35 ms For use with IZMX16..., IZMX40... INX16..., INX40... Instructions An additional control circuit terminal block is required for retrofitting.

For fixed mounting circuit-breakers?#156593 and withdrawable unit circuit-breakers ?#156590 Notes Suitable for continuous commands (100% DF)

The ON command can only be accepted if the circuit-breaker is OFF and ready to be switched. If, for example, there is a 100% DF signal at the closing release and the circuit-breaker interlock is then removed, the circuit-breaker will not switch ON. However, this can be ensured automatically by connecting it in series with an LCS auxiliary contact.

, Design verification as per IEC/EN 61439

Operating ambient temperature min. -25 °C Operating ambient temperature max. +70 °C , Technical data ETIM 7.0
Low-voltage industrial components (EG000017) / Shunt release (for power...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX-SR230AD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.