

**INDUSTRIAL COMPONENT DATA**

# M22-XW 216405 Y7-216405 EATON ELECTRIC Plunger Bridge

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XW

|                                           |                 |                                             |
|-------------------------------------------|-----------------|---------------------------------------------|
| <div>PRODUCT IMAGE\n\nNOT AVAILABLE</div> | Manufacturer    | EATON - MOELLER                             |
|                                           | MPN / Reference | M22-XW                                      |
|                                           | Catalog number  | Y7-216405                                   |
|                                           | Category        | Accessories/spare parts for command devices |
|                                           | Minimum order   | 1 Pcs                                       |
|                                           | Document ID     | EO-F23D1CACC0                               |
|                                           | Generated       | 2026-07-31                                  |

## Product Overview

Plunger Bridge

M22-XW

Eaton Moeller® series M22 Plunger Bridge

Plunger bridge, black, for actuating the middle contact element of the non-illuminated 3-position selector switch actuator M22-W...3

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Auxiliary Control and Signalling Elements |
|--------------|-------------------------------------------------------------|

## Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Plunger bridge Catalog Number 216405 Model Code M22-XW EAN 4015082164058 Product Length/Depth 19 mm Product Height 16 mm Product Width 11 mm Product Weight 0.32 g

Compliances CE Marked Certifications UL 508

EN 60947-5

CSA Std. C22.2 No. 94-91

CSA Std. C22.2 No. 14-05

IEC 60947-5

CSA

CSA File No.: 012528

CSA Class No.: 3211-03

CSA-C22.2 No. 94-91

CSA-C22.2 No. 14-05

IEC/EN 60947-5

UL File No.: E29184

CE

UL

UL Category Control No.: NKCR Features & Functions

Functions For actuating the middle contact element of the M22-W...3 non-illuminated 3-position selector switch actuator

General

Accessory/spare part type Accessory

Spare part Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication

Connection to SmartWire-DT No Contacts

Force for positive opening - min 0 N Design verification

Equipment heat dissipation, current-dependent P<sub>vid</sub> 0 W Heat dissipation capacity P<sub>diss</sub> 0 W Heat dissipation per pole,

current-dependent P<sub>vid</sub> 0 W Rated operational current for specified heat dissipation (I<sub>n</sub>) 0 A Static heat dissipation,

non-current-dependent P<sub>vs</sub> 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance

of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XW with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.