

## INDUSTRIAL COMPONENT DATA

# M22-XC-Y 216407 Y7-216407 EATON ELECTRIC 216407 M22-XC-Y

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XC-Y



|                 |                                             |
|-----------------|---------------------------------------------|
| Manufacturer    | EATON - MOELLER                             |
| MPN / Reference | M22-XC-Y                                    |
| Catalog number  | Y7-216407                                   |
| Category        | Accessories/spare parts for command devices |
| Minimum order   | 1 Pcs                                       |
| Document ID     | EO-63A31F7F3E                               |
| Generated       | 2026-08-02                                  |

## Product Overview

216407 M22-XC-Y

M22-XC-Y

Eaton Moeller® series M22 Coding part M22-XC-Y

Coded partial set for converting between maintained and spring-return function with selection keys of the RQM system 22.3 mm

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

## Additional Product Information

## General specifications

Product Name Eaton Moeller® series M22 Accessory Coding kit Catalog Number 216407 Model Code M22-XC-Y EAN 4015082164072 Product Length/Depth 19 mm Product Height 16 mm Product Width 11 mm Product Weight 0.002 kg Certifications UL/CSA certification not required Catalog Notes Not for key-operated button for master key systems Features & Functions

Color Yellow Functions For converting between stay-put and spring-return function General

Accessory/spare part type Accessory Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication

Connection to SmartWire-DT No Contacts

Force for positive opening - min 0 N Design verification

Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation capacity Pdiss 0 W Heat dissipation per pole,

current-dependent P<sub>vid</sub> 0 W Rated operational current for specified heat dissipation (I<sub>n</sub>) 0 A Static heat dissipation, non-current-dependent P<sub>vs</sub> 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Please enquire 10.2.5 Lifting Does not apply,....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XC-Y with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.