

INDUSTRIAL COMPONENT DATA

DILM250-S-XSP/E(220-240V50/60HZ) 274202 Y7-274202

EATON ELECTRIC 274202

DILM250-S-XSP/E(220-240V50/60HZ)

Brand: EATON - MOELLER | Manufacturer Part Number: DILM250-S-XSP/E(220-240V50/60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM250-S-XSP/E(220-240V50/60HZ)
Catalog number	Y7-274202
Category	Coil for relay
Minimum order	1 Pcs
Document ID	EO-2CB9AB6EC0
Generated	2026-08-06

Product Overview

DILM250-S-XSP/E(220-240V50/60HZ)

Eaton Moeller® series DILM Replacement coil, 220 V 50 Hz, 240 V 60 Hz, AC operation, For use with: DILM250-S, DILM300A-S

Replacement coil, Actuating voltage: 220 V 50 Hz, 240 V 60 Hz, Voltage AC/DC: AC operation, For use with: DILM250-S, DILM300A-S

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors more than 170 A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM replacement coil Catalog Number 274202 Model Code

DILM250-S-XSP/E(220-240V50/60HZ) EAN 4015082742027 Product Length/Depth 100 mm Product Height 175 mm

Product Width 135 mm Product Weight 1.19 kg Compliances CE Marked Certifications CSA Std. C22.2 No. 14-05
UL 508

IEC 60947-4-1

EN 60947-4-1

UL File No.: E29096

CSA-C22.2 No. 14-05

CE

CSA

CSA File No.: 1017510

CSA Class No.: 3211-04

IEC/EN 60947-4-1

UL

UL Category Control No.: NLDX Global

Accessories Individual coils Product category Accessories Used with DILM185-S/225-S/250 General

Ambient operating temperature - min -40 °C Ambient operating temperature - max 60 °C Product category Accessories

Used with DILM185-S/225-S/250 Switching capacity

Rated control supply voltage (Us) at AC, 50 Hz - min 220 V Rated control supply voltage (Us) at AC, 50 Hz - max 240 V

Rated control supply voltage (Us) at AC, 60 Hz - min 220 V Rated control supply voltage (Us) at AC, 60 Hz - max 240 V

Rated control supply voltage (Us) at DC - min 0 V Rated control supply voltage (Us) at DC - max 0 V Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 220 V Rated control supply voltage (Us) at AC, 50 Hz - max 240 V

Rated control supply voltage (Us) at AC, 60 Hz - min 220 V Rated control supply voltage (Us) at AC, 60 Hz - max 240 V

Rated control supply voltage (Us) at DC - min 0 V Rated control supply voltage (Us) at DC - max 0 V Contacts

10.2.2 Corrosion resistance Meets the prod...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM250-S-XSP/E(220-240V50/60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.