

INDUSTRIAL COMPONENT DATA

KSK-N 178903 Y7-178903 EATON ELECTRIC Combination plug-in terminal KSK individual blue for neutral conductor

Brand: EATON - MOELLER | Manufacturer Part Number: KSK-N



Manufacturer	EATON - MOELLER
MPN / Reference	KSK-N
Catalog number	Y7-178903
Category	Single- and multi-pole terminal strip
Minimum order	1 Pcs
Document ID	EO-EC93D9FAE4
Generated	2026-08-06

Product Overview

Combination plug-in terminal KSK; individual; blue for neutral conductor
KSK-N

Eaton xComfort KLV LV systems Final Distribution Boards. Combination plug-in terminal KSK, individual, blue for neutral conductor

Combination plug-in terminal KSK, individual, blue for neutral conductor, 63A / 400V AC, degree of protection IP2X, 1x screw connection for 2.5-25 mm² (solid/stranded) or 2.5-16 mm² (flexible with professionally crimped ferrule) and 7x plug-in connections for 0.5-4 mm² (solid/stranded) or 2.5-16 mm² (flexible with professionally crimped ferrule).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Compact Distribution Boxes

Additional Product Information

General specifications

Product Name Eaton xComfort KLV plug-type terminal Catalog Number 178903 Model Code KSK-N EAN 4015081742202

Product Length/Depth 19.5 mm Product Height 17 mm Product Width 55 mm Product Weight 0.04 kg Compliances RoHS conform Product specifications

Features Halogen free Degree of protection IP2X Used with Individual KSK combination plug-in terminal

Accessory consideration

KLV distribution board

KLV Accessories Type Accessory/spare part type General Operating temperature - min 35 °C Width/grid dimension 55 mm

Rated operational voltage (Ue) - max 400 V Mounting method Direct mounting Number Of Poles Single-pole Connection

position Inclined Color Blue Electrical connection 1 type Screw connection Insulation body material Thermoplastic
Connectable conductor cross section (fine strand) - max 25 mm² Connectable conductor cross section (fine strand) - min 2.5 mm² Connectable conductor cross section (fine-strand) with cable end sleeve - max 16 mm² Connectable conductor cross section (fine-strand) with cable end sleeve - min 2.5 mm² Connectable conductor cross section (multi-wired) - max 25 mm² Connectable conductor cross section (multi-wired) - min 2.5 mm² Connectable conductor cross section (solid-core) - max 25 mm² Connectable conductor cross section (solid-core) - min 2.5 mm² Nominal current 63 A Drill hole distance (centrically) 1 mm Mounting height - min 17 mm Number of clamp positions per level 8 Operating temperature - max 35 °C
Electrical connection 2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / KSK-N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.