

INDUSTRIAL COMPONENT DATA

KSK-PE 178904 Y7-178904 EATON ELECTRIC Combination plug-in terminal KSK individual green for neutral conduct..

Brand: EATON - MOELLER | Manufacturer Part Number: KSK-PE



Manufacturer	EATON - MOELLER
MPN / Reference	KSK-PE
Catalog number	Y7-178904
Category	Single- and multi-pole terminal strip
Minimum order	1 Pcs
Document ID	EO-7B3966E5CF
Generated	2026-08-04

Product Overview

Combination plug-in terminal KSK; individual; green for neutral conductor

KSK-PE

Combination plug-in terminal KSK, individual, green for protective conductor, 63A / 400V AC, degree of protection IP2X, 1x screw connection for 2.5-25 mm² (solid/stranded) or 2.5-16 mm² (flexible with professionally crimped ferrule) and 7x plug-in connections for 0.5-4 mm² (solid/stranded) or 2.5-16 mm² (flexible with professionally crimped ferrule).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Compact Distribution Boxes

Additional Product Information

Combination plug-in terminal KSK; individual; green for neutral conductorCombination plug-in terminal KSK, individual, green for protective conductor, 63A / 400V AC, degree of protection IP2X, 1x screw connection for 2.5-25 mm² (solid/stranded) or 2.5-16 mm² (flexible with professionally crimped ferrule) and 7x plug-in connections for 0.5-4 mm² (solid/stranded) or 2.5-16 mm² (flexible with professionally crimped ferrule).

General specificationsProduct nameEaton xComfort KLV plug-type terminalPart no.KSK-PEEAN4015081742219Product Length/Depth19.5 millimetreProduct height17 millimetreProduct width55 millimetreProduct weight0.04 kilogramCompliancesRoHS conformProduct TradenamexComfort KLVProduct TypeAccessoriesProduct Sub TypePlug-type terminalDelivery programTypeAdditional equipment KLV distribution boardAccessory/spare part typeGeneralColorGreenNominal current63 ATechnical Data - ElectricalRated operational voltage (Ue) - max400 VTechnical Data - MechanicalMounting height - min17 mmMounting methodDirect mountingDegree of protectionIP2XNumber of clamp positions per level8Connection positionInclinedOperating temperature -

min35 °COperating temperature - max35 °CConnectable conductor cross section (fine strand) - min2.5 mm²Connectable conductor cross section (fine strand) - max25 mm²Connectable conductor cross section (multi-wired) - min2.5 mm²Connectable conductor cross section (multi-wired) - max25 mm²Connectable conductor cross section (solid-core) - min2.5 mm²Connectable con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / KSK-PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.