

INDUSTRIAL COMPONENT DATA

PKNM-16/1N/C/03-G-MW 236222 EATON ELECTRIC RCD/MCB combination switch, 16A, 300mA, miniature circuit-br. typ..

Brand: EATON - MOELLER | Manufacturer Part Number: PKNM-16/1N/C/03-G-MW



Manufacturer	EATON - MOELLER
MPN / Reference	PKNM-16/1N/C/03-G-MW
Catalog number	236222
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-DF2847BEC1
Generated	2026-08-04

Product Overview

RCD/MCB combination switch, 16A, 300mA, miniature circuit-br. type C trip characteristic, 1-ph+N, residual current circuit-br. trip characteristic: AC

Combined Int. PKNM, 1P+N, C-curve, 16A, 300mA

High-quality residual current circuit-breaker/miniature circuit-breaker with overcurrent protection independent of mains voltage; contact position display red-green; terminal rear plug protection; tri-stable slide catch-enables removal from an existing closure assembly; comprehensive accessory product range can be retrofitted; wide range of rated fault currents; rated operational currents up to 40 A; trip types B,C,D; rated switching capacity 10 kA; suitable for use in the free (on-site power and outdoor distribution board) to -25 °C; suitable for use in the free (on-site power and outdoor distribution board) to -25 °C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Tertiary and Differential

Additional Product Information

RCD/MCB combination switch, 16A, 300mA, miniature circuit-br. type C trip characteristic, 1-ph+N, residual current circuit-br. trip characteristic: ACHigh-quality residual current circuit-breaker/miniature circuit-breaker with overcurrent protection independent of mains voltage; contact position display red-green; terminal rear plug protection; tri-stable slide catch-enables removal from an existing closure assembly; comprehensive accessory product range can be retrofitted; wide range of rated fault currents; rated operational currents up to 40 A; trip types B,C,D; rated switching capacity 10 kA; suitable for use in the free (on-site power and outdoor distribution board) to -25 °C; suitable for use in the free (on-site power and outdoor distribution board) to -25 °CDelivery program

Basic function Combined RCD/MCB devices Number of poles 1 pole+N Tripping characteristic C Application Switchgear for residential and commercial applications Rated current [In] 16 A Rated switching capacity according to IEC/EN 61009 10 kA Rated fault current [I_n] 0.3 A Type Type G (ÖVE E 8601) Tripping Short time-delayed s... Product range PKNM Sensitivity AC current sensitive Impulse withstand current Surge-proof, 3 kA Technical data Electrical Sensitivity AC current sensitive Design verification as per IEC/EN 61439 Technical data for design verification Rated operational current for specified heat dissipation [In] 16 A Heat dissipation per pole, current-dependent [P_{vid}] 0 W Equipment heat dissipation, current-dependent [P_{vid}] 3....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKNM-16/1N/C/03-G-MW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.