

INDUSTRIAL COMPONENT DATA

11100AQD07 135557 Y7-135557 EATON ELECTRIC Thru-beam photoelectric sensor, transmitter, Sn 6m, 4L, 10-30VDC,..

Brand: EATON - MOELLER | Manufacturer Part Number: 11100AQD07



Manufacturer	EATON - MOELLER
MPN / Reference	11100AQD07
Catalog number	Y7-135557
Category	Through beam photoelectric sensor
Minimum order	1 Pcs
Document ID	EO-7B27C81B3C
Generated	2026-08-03

Product Overview

Thru-beam photoelectric sensor, transmitter, Sn=6m, 4L, 10-30VDC, NPN, PNP, M18, insulated material, M12 11100AQD07

Eaton Moeller® series E58 Thru-beam photoelectric sensor, transmitter, Sn=6m, 4L, 10-30VDC, NPN, PNP, M18, insulated material, M12 11100AQD07

Optical sensor, comet series, polyurethane housing with 18 mm diameter and flattened side for extra mounting comfort, IP67_x, high vibration and impact resistance . The Comet series features one-way light barrier reflection light barrier diffuse mode sensors with or without background suppression, simplified installation using visible scanning beams, selectable light or dark operation, short-circuit protection, optical cross-talk protection at closely mounted sensors, adjustable gain factor, optional connection of fiber-optic light guides

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Sensors
--------------	---------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series E58 Thru-beam photoelectric sensor Catalog Number 135557 Model Code 11100AQD07 EAN 4015081323500 Product Length/Depth 158.75 mm Product Height 50.8 mm Product Width 133.35 mm Product Weight 0.32 kg Certifications CSA-C22.2 No. 14

CSA

CSA File No.: 50513

IEC/EN 60947-5-2

UL Category Control No.: NRKH, NRKH7

UL 508

UL

CE

CSA Class No.: 3211-07

UL File No.: E117028 Product specifications

Type Optical sensors Features Straight beam Device type Transmitter Electric connection type Connector M12 Fitted with: Transmitter (for combination with detector) Enclosure material Plastic Enclosure type Cylinder, screw-thread Explosion safety category for dust None Explosion safety category for gas None Functions Short-circuit protection Thru-light beam

Protection against polarity reversal Voltage type DC Wire size 0 Connection type Plug-in connection M12 x 1 4-wire Cable sheath material Polyurethane (PUR) Light type Polarity free red light Degree of protection IP67

NEMA 6 Interface type Other LED indicator Status indication of Operating voltage: Red LED Switch function type Other Load current Max. 100 mA (Ie, PNP)

Max. 250 mA (Ie, NPN, 120 > 50°C) Laser protection class None Operation agent-safety class Safety class 2 Shock resistance 100 g, Mechanical, Shock duration 3 ms Optical surface material Plastic Output current (mA) - max 100 mA Output current at protected output - max 0 mA Rated control supply voltage (Us) at AC, 50 Hz - ma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 11100AQD07 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.