

INDUSTRIAL COMPONENT DATA

COM-MPB1-TP 139850 4560813 EATON ELECTRIC

Communication module multiple protocol board for XV-4...

Brand: EATON - MOELLER | Manufacturer Part Number: COM-MPB1-TP



Manufacturer	EATON - MOELLER
MPN / Reference	COM-MPB1-TP
Catalog number	4560813
Category	PLC communication module
Minimum order	1 Pcs
Document ID	EO-23EED75278
Generated	2026-07-31

Product Overview

Communication module multiple protocol board for XV-4...

Multi-Protocol Communication Module for XV-4...

Thanks to this optional plug-in communication module (in devices from 10.4 inches, two cards can be plugged in), the XV-400 devices cover more than 100 communication protocols.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > HMI Touch Terminals
--------------	---------------------------------------

Additional Product Information

Communication module multiple protocol board for XV-4... EL-Nummer (Norway) 4560813 Thanks to this optional plug-in communication module (in devices from 10.4 inches, two cards can be plugged in), the XV-400 devices cover more than 100 communication protocols. [Delivery program

Accessories Communication cards Description Multiple protocol board Supported protocols Eaton Suconet

Matsushita FP series

Mitsubishi A-Series/F-Series

Omron C-H-K-Series

Telemecanique Unitelway new

See manual for other protocols , Technical data

Power supply Note on heat dissipation not relevant Environmental conditions TemperatureOperating ambient temperature min. 0 °C TemperatureOperating ambient temperature max. +55 °C , Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per

pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 0 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. 0 °C Operating ambient temperature max. +55 °C IEC/EN 61439 design verification 10.2 Strength of materials and parts10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.2 Verification of resistance of insulat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / COM-MPB1-TP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.