

INDUSTRIAL COMPONENT DATA

COM-PDP-TP 139849 4560812 EATON ELECTRIC

Communication module Profibus DP slave for XV-4...

Brand: EATON - MOELLER | Manufacturer Part Number: COM-PDP-TP



Manufacturer	EATON - MOELLER
MPN / Reference	COM-PDP-TP
Catalog number	4560812
Category	PLC communication module
Minimum order	1 Pcs
Document ID	EO-3023A836BF
Generated	2026-08-01

Product Overview

Communication module Profibus DP slave for XV-4...

Profibus DP Slave Communication Module for XV-4...

Thanks to this optional plug-in communication module (in devices from 10.4 inches, two cards can be plugged in), the XV-400 devices cover more than 100 communication protocols.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > HMI Touch Terminals
--------------	---------------------------------------

Additional Product Information

General specifications

Product Name Eaton XN Communication module Catalog Number 139849 Model Code COM-PDP-TP EAN

7640130092372 Product Length/Depth 145 mm Product Height 20 mm Product Width 108 mm Product Weight 0.112 kg

Certifications CSA-C22.2 No. 60950-1

UL File No.: Refer to main component information

UL Recognized

CSA File No.: Refer to main component information

CE

UL Category Control No.: NWGQ2, NWGQ8

Certified by UL for use in Canada

IEC/EN 61131-2

UL 60950-01 Features & Functions

Fitted with: Potential separation General

Suitable for Analog to basic device, (UL/CSA) Climatic environmental conditions

Ambient operating temperature - min 0 °C Ambient operating temperature - max 55 °C Electrical rating

Power consumption 2 W Communication

Protocol Profibus DP-Slave (12 MBaud)

PROFIBUS Safety

Explosion safety category for dust ATEX dust-ex-protection, Cat. 3D Explosion safety category for gas None Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance

of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / COM-PDP-TP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.