

INDUSTRIAL COMPONENT DATA

LZMB2-A200-I 111923 Y7-111923 EATON ELECTRIC

Circuit-breaker, 3 p, 200A

Brand: EATON - MOELLER | Manufacturer Part Number: LZMB2-A200-I



Manufacturer	EATON - MOELLER
MPN / Reference	LZMB2-A200-I
Catalog number	Y7-111923
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-A456EF512B
Generated	2026-08-05

Product Overview

Circuit-breaker, 3 p, 200A

LZMB2-A200-I

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Circuit Breakers LZM

Additional Product Information

Circuit-breaker, 3 p, 200A

General specifications
Product nameEaton Moeller series Power Defense molded case circuit-breaker
Part no.LZMB2-A200-IEAN4015081114719
Product Length/Depth142 millimetre
Product height185 millimetre
Product width105 millimetre
Product weight2.336 kilogram
CompliancesRoHS conform
CertificationsVDE 0660

IEC

IEC/EN 60947
Product TradenamePower Defense
Product TypeMolded case circuit breaker
Product Sub TypeNone
Delivery programApplicationUse in unearthed supply systems at 440 V
TypeCircuit breaker
Circuit breaker frame typeLZM2
Number of polesThree-pole
Amperage Rating200 A
Release systemThermomagnetic release
FeaturesMotor drive optional
Protection unitSpecial featuresMaximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I_{cn})
Rated current = rated uninterrupted current: 200 A
Technical Data - Electrical
Voltage rating440 V - 440 V
Rated insulation voltage (U_i)690 V
AC
Rated impulse withstand voltage (U_{imp}) at auxiliary contacts6000 V
Rated impulse withstand voltage (U_{imp}) at main contacts8000 V
Rated operational current200 A (660-690 V AC-3, making and breaking capacity)
300 A (415 V AC-1, making and breaking capacity)

200 A (415 V AC-3, making and breaking capacity)

300 A (380/400 V AC-1, making and breaking capacity) Instantaneous current setting (Ii) - min1200 A Instantaneous current

setting (Ii) - max2000 A Overload current setting (Ir) - min160 A O...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LZMB2-A200-I with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.