

## INDUSTRIAL COMPONENT DATA

# LZMC1-ASF40-I 111881 Y7-111881 EATON ELECTRIC

## Circuit-breaker, 3 p, 40A

Brand: EATON - MOELLER | Manufacturer Part Number: LZMC1-ASF40-I



|                 |                                                                   |
|-----------------|-------------------------------------------------------------------|
| Manufacturer    | EATON - MOELLER                                                   |
| MPN / Reference | LZMC1-ASF40-I                                                     |
| Catalog number  | Y7-111881                                                         |
| Category        | Power circuit-breaker for trafo/generator/installation protection |
| Minimum order   | 1 Pcs                                                             |
| Document ID     | EO-6AD17BFBEE                                                     |
| Generated       | 2026-08-05                                                        |

### Product Overview

Circuit-breaker, 3 p, 40A

LZMC1-ASF40-I

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Circuit Breakers LZM

### Additional Product Information

Circuit-breaker, 3 p, 40A Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228) Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection ([email protected] [AJZ716013]) Rated permanent current I<sub>u</sub> 40 A Rated voltage 690 - 690 V Rated short-circuit breaking capacity I<sub>cu</sub> at 400 V, 50 Hz 36 kA Overload release current setting 32 - 40 A Adjustment range short-term delayed short-circuit release 0 - 0 A Adjustment range undelayed short-circuit release 320 - 400 A Integrated earth fault protection No Type of electrical connection of main circuit Frame clamp Device construction Built-in device fixed built-in technique Suitable for DIN rail (top hat rail) mounting No DIN rail (top hat rail) mounting optional Yes Number of auxiliary contacts as normally closed contact 0 Number of auxiliary contacts as normally open contact 0 Number of auxiliary contacts as change-over contact 0 With switched-off indicator No With under voltage release No Number of poles 3 Position of connection for main current circuit Front side Type of control element Rocker lever Complete device with protection unit Yes Motor drive integrated No Motor drive optional No Degree of protection (IP) IP20

ETIM for 111881 Low-voltage industrial controls and switchgear (EC000228)

Feature Name

Feature Value

Rated permanent current I<sub>u</sub> (EF00138...**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send EATON - MOELLER / LZMC1-ASF40-I with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.