

INDUSTRIAL COMPONENT DATA

LZMC2-4-A250/160-I 111950 EATON ELECTRIC

Circuit-breaker, 4 p, 200A, 160A, in 4th pole

Brand: EATON - MOELLER | Manufacturer Part Number: LZMC2-4-A250/160-I



Manufacturer	EATON - MOELLER
MPN / Reference	LZMC2-4-A250/160-I
Catalog number	111950
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-3D9FE05820
Generated	2026-08-03

Product Overview

Circuit-breaker, 4 p, 200A, 160A, in 4th pole

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers LZM
--------------	--

Additional Product Information

Delivery programme Product range Circuit-breaker
 Protective function System and cable protection
 Standard/Approval IEC
 Installation type Fixed
 Release system Thermomagnetic release
 Construction size LZM2
 Description Set value in neutral conductor is synchronous with set value I_r of main pole.
 Number of poles 4 pole
 Standard equipment Screw connection
 Switching capacity
 400/415 V 50 Hz I_{cu} kA 36
 Rated current = rated uninterrupted current
 Rated current = rated uninterrupted current $I_n = I_u$ A 250
 Neutral conductor % of phase conductor CSA 60
 Neutral conductor protection Reduced neutral conductor protection

Setting range

Overload trip

General

Standards IEC/EN 60947, VDE 0660

Protection against direct contact Finger and back-of-hand proof to VDE 0106 part 100

Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Mechanical shock resistance (10 ms half-sinusoidal shock) according to IEC 60068-2-27 g 20 (half-sinusoidal shock 20 ms)

Safe isolation to EN 61140

Between auxiliary contacts and main contacts V AC 500

between the auxiliary contacts V AC 300

Mounting position Vertical and 90° in all directions

Technical data for design verification

Rated operational current for specified heat dissipation In A 250

Equipment heat dissipation, current-dependent P_{vid} W 58.125

IEC/EN 61439 design verification

10.2 Strength of materials and parts

10.2.2 Corrosion resistance Meets the product standard's requirements.

10.2.3.1 Verification of thermal stabi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LZMC2-4-A250/160-I with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.