

INDUSTRIAL COMPONENT DATA

NZMN2-A250-S5-10 268258 Y7-268258 EATON ELECTRIC

Power Distribution Components IEC Moulded case circuit brea..

Brand: EATON - MOELLER | Manufacturer Part Number: NZMN2-A250-S5-10



Manufacturer	EATON - MOELLER
MPN / Reference	NZMN2-A250-S5-10
Catalog number	Y7-268258
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-9B06AB0ED7
Generated	2026-08-05

Product Overview

Power Distribution Components IEC Moulded case circuit breaker
Circuit Breaker , 3P, Iu: 250A
Molded case circuit breaker
NZMN2-A250-S5-10. Circuit-breaker

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

Molded case circuit breaker
General specifications
Product name Eaton Moeller series NZM molded case circuit breaker thermo-magnetic
Part no. NZMN2-A250-S5-10
EAN 4015082682583
Product Length/Depth 149 millimetre
Product height 184 millimetre
Product width 105 millimetre
Product weight 2.345 kilogram
Certifications IEC/EN 60947
IEC
Product Trade name NZM
Product Type Molded case circuit breaker
Product Sub Type Thermo-magnetic
Delivery program Application 690 V
Type Circuit breaker
Circuit breaker frame type NZM2
Number of poles Three-pole
Amperage Rating 250 A
Release system Thermomagnetic release
Special features Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn)
Rated current = rated uninterrupted current: 250 A
Technical Data - Electrical
Voltage rating 690 V AC
Rated insulation voltage (Ui) 1000 V AC
Rated impulse withstand voltage (Uimp) at auxiliary contacts 6000 V
Rated impulse withstand voltage

(Uimp) at main contacts 8000 V Rated short-time withstand current ($t = 0.3$ s) 1.9 kA Rated short-time withstand current ($t = 1$ s) 1.9 kA Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 230 V, 50/60 Hz 85 kA Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz 50 kA Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 440 V, 50/60 Hz 35 kA Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 525 V, 50/60 Hz 25 kA Rated short-circuit breaking capacity....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMN2-A250-S5-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.