

INDUSTRIAL COMPONENT DATA

EC4P-222-MTXD1 106399 0004519744 EATON ELECTRIC Compact PLC, 24 V DC, 12DI(of 4AI), 8DO(T), ethernet, CAN, d..

Brand: EATON - MOELLER | Manufacturer Part Number: EC4P-222-MTXD1



Manufacturer	EATON - MOELLER
MPN / Reference	EC4P-222-MTXD1
Catalog number	0004519744
Category	PLC device set
Minimum order	1 Pcs
Document ID	EO-C311965676
Generated	2026-08-03

Product Overview

Compact PLC, 24 V DC, 12DI(of 4AI), 8DO(T), ethernet, CAN, display

EC4P-222-MTXD1

Compact controller for small and medium-sized automation tasks, programming according to IEC 61131 (CoDeSys), the Ethernet interface and the serial interface (ec4p-222 types) are for the purpose of programming, the communication via UDP and Modbus as well as connection of OPC clients

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > EC4P PLCs
--------------	-----------------------------

Additional Product Information

EL-Nummer (Norway)4519744Compact PLC, 24 V DC, 12DI(of 4AI), 8DO(T), ethernet, CAN, displayCompact controller for small and medium-sized automation tasks, programming according to IEC 61131 (CoDeSys), the Ethernet interface and the serial interface (ec4p-222 types) are for the purpose of programming, the communication via UDP and Modbus as well as connection of OPC clientsDelivery program

Expandable: Inputs/outputs and bus systems

individual laser inscription possible with EC4-COMBINATION-*DescriptioneasyNet/CANopen® and Ethernet on

boardInputsDigital12of which can be used as analog4OutputsTransistor8Additional featuresDisplay & keypad?Supply

voltage24 V DCTechnical data

GeneralDimensions (W x H x D)107.5 x 90 x 72 without/79 with adapter for MCC (6 SU) mmWeight0.3 kgMountingTop-hat

rail IEC/EN 60715, 35 mm or screw fixing using 3 fixing brackets ZB4-101-GF1 (accessories) Terminal capacities Solid 0.2/4 (AWG 22 - 12) mm² Flexible with ferrule 0.2/2.5 (AWG 22 - 12) mm² Standard screwdriver 0.8 x 3.5 mm Max. tightening torque 0.6 Nm Climatic environmental conditions Operating ambient temperature -25 to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2 °C Condensation Take appropriate measures to prevent condensation LCD display (clearly legible) 0 - 55 °C Storage [?] -40 - +70 °C Relative humidity, non-condensing (IEC/EN 60068-2-30) 5 - 95 % Air pressure (operation) 1080 - 1080 hPa Ambient conditions, mechanical Protection type (IEC/EN 60529, EN50178, VBG 4) IP20 Vibrations (IEC/EN 60068-2-6) Con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EC4P-222-MTXD1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.